# **Product datasheet**

Specifications





# Multi 9 - C60BP - MCB - 1P - 15 A - D Curve - 277 V - 10 kA - UL 489

M9F43115

EAN Code: 3606481170118

#### Main

| Mann                      |  |
|---------------------------|--|
| Range                     | Multi9   |
| Product Name              | Multi9 C60   |
| Product Or Component Type | Miniature circuit-breaker  |
| Device Short Name         | C60BP  |
| Device Application        | Distribution   |
| Poles Description         | 1P   |
| Number Of Protected Poles | 1  |
| [In] Rated Current        | 15 A at 25 °C conforming to EN/IEC 60947-2   |
| Network Type              | AC<br>DC   |
| Trip Unit Technology      | Thermal-magnetic   |
| Curve Code                | D  |
| Breaking Capacity         | 3 kA Icu at 415 V AC conforming to EN/IEC 60947-2<br>10 kA Icu at 240 V AC conforming to EN/IEC 60947-2<br>20 kA Icu at 60 V DC conforming to EN/IEC 60947-2<br>3 kA Icu at 415 V AC conforming to GB 14048.2<br>10 kA Icu at 240 V AC conforming to GB 14048.2<br>20 kA Icu at 60 V DC conforming to GB 14048.2<br>10 kA AIR at 277 V AC conforming to UL 489<br>14 kA AIR at 240 V AC conforming to UL 489<br>14 kA AIR at 120 V AC conforming to UL 489<br>10 kA AIR at 277 V AC conforming to UL 489<br>10 kA AIR at 277 V AC conforming to UL 489<br>10 kA AIR at 277 V AC conforming to CSA C22.2 No 5<br>14 kA AIR at 120 V AC conforming to CSA C22.2 No 5<br>10 kA AIR at 120 V AC conforming to CSA C22.2 No 5 |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2   |
| Standards                 | EN/IEC 60947-2<br>GB 14048.2<br>UL 489<br>CSA C22.2 No 5   |
| Product Certifications    | IEC<br>CCC<br>CSA<br>UL  |

### Complementary

| [Ue] Rated Operational Voltage | 240 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>60 V DC |
|--------------------------------|---|
| Magnetic Tripping Limit        | 12 x ln +/- 20 % AC<br>17 x ln +/- 20 % DC        |

| [Ics] Rated Service Breaking              | 2.25 kA 75 % conforming to EN/IEC 60947-2 - 415 V AC                                  |
|---|---|
| Capacity                                  | 7.5 kA 75 % conforming to EN/IEC 60947-2 - 240 V AC                                   |
|   | 2.25 kA 75 % conforming to GB 14048.2 - 415 V AC                                      |
|   | 7.5 kA 75 % conforming to GB 14048.2 - 240 V AC                                       |
|   | 15 kA 75 % conforming to GB 14048.2 - 60 V DC   |
|   | 15 kA 75 % conforming to EN/IEC 60947-2 - 60 V DC                                     |
| Ui] Rated Insulation Voltage              | 500 V AC conforming to EN/IEC 60947-2   |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kV conforming to EN/IEC 60947-2   |
| Contact Position Indicator                | Yes   |
| Control Type                              | Toggle  |
| Local Signalling                          | ON/OFF indication   |
| Mounting Mode                             | Clip-on   |
| Mounting Support                          | DIN rail  |
| 9 Mm Pitches                              | 2   |
| Height                                    | 103 mm  |
| Width                                     | 18 mm   |
| Depth                                     | 72 mm   |
| Colour                                    | Grey  |
| Mechanical Durability                     | 20000 cycles  |
| Electrical Durability                     | 10000 cycles  |
| Provision For Padlocking                  | Padlockable   |
| Connections - Terminals                   | Tunnel type terminal (top or bottom)125 mm² (AWG 18AWG 8) - rigid                     |
|   | Tunnel type terminal (top or bottom)116 mm <sup>2</sup> (AWG 18AWG 8) - flexible with |
|   | ferrule   |
|   | Tunnel type terminal (top or bottom)116 mm <sup>2</sup> (AWG 18AWG 8) - flexible      |
| Wire Stripping Length                     | 14 mm for top or bottom connection  |
| Tightening Torque                         | 2.5 N.m top or bottom   |
| Earth-Leakage Protection                  | Without   |
|   |   |

#### Environment

| Ip Degree Of Protection                  | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
|--|--|
| Pollution Degree                         | 3 conforming to EN/IEC 60947-2   |
| Tropicalisation                          | 2 conforming to IEC 60068-1  |
| Relative Humidity                        | 95 % at 55 °C  |
| Operating Altitude                       | 02000 m  |
| Ambient Air Temperature For<br>Operation | -3070 °C   |
| Ambient Air Temperature For<br>Storage   | -4080 °C   |

# **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 7.5 cm  |
| Package 1 Width              | 1.8 cm  |
| Package 1 Length             | 10.3 cm |

| Package 1 Weight             | 120 g     |
|------------------------------|-----------|
| Unit Type Of Package 2       | BB1       |
| Number Of Units In Package 2 | 12        |
| Package 2 Height             | 8.5 cm    |
| Package 2 Width              | 10.8 cm   |
| Package 2 Length             | 22 cm     |
| Package 2 Weight             | 1.505 kg  |
| Unit Type Of Package 3       | \$03      |
| Number Of Units In Package 3 | 108       |
| Package 3 Height             | 30 cm     |
| Package 3 Width              | 30 cm     |
| Package 3 Length             | 40 cm     |
| Package 3 Weight             | 13.993 kg |

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information                       |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |