Product data sheet

Specifications





Multi9 - Vigi C60 - 3P - 63A - class AC - 230/400 V - 30mA

M9V11363

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 674.00 USD

Main

Range	Multi9
Product Or Component Type	Add-on residual current devices
Device Short Name	Vigi C60
Range Compatibility	Multi9 Multi9 C60 C60N Multi9 Multi9 C60 C60L Multi9 Multi9 C60 C60H Multi9 Multi9 C60 C60CTRL
Poles Description	3P
Line Rated Current	63 A EN/IEC 61009-1
Network Type	AC
Network Frequency	50 Hz
[Ue] Rated Operational Voltage	400/415 V AC 50 Hz
Earth-Leakage Sensitivity	30 mA EN/IEC 61009-1
Earth-Leakage Protection Time Delay	Instantaneous
Earth-Leakage Protection Class	Туре АС
9 Mm Pitches	7

Complementary

· · · · · · · · · · · · · · · · J	
Residual Current Tripping Technology	Voltage independent
[Ui] Rated Insulation Voltage	500 V AC 50 Hz EN/IEC 61009-1
[Uimp] Rated Impulse Withstand Voltage	4 kVEN/IEC 61009-1
Local Signalling	Fault indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
Electrical Connection To Mcb	By screws
Height	3.43 in (87 mm)
Width	2.48 in (63 mm)
Depth	2.91 in (74 mm)
Net Weight	7.41 oz (210 g)
Color	Gray
Connections - Terminals	Tunnel type terminal bottom) 0.000.05 in² (135 mm²) - rigid Tunnel type terminal bottom) 0.000.04 in² (125 mm²) - flexible

Tunnel type terminal bottom) 0.00...0.04 in² (1...25 mm²) - flexible with ferrule

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Wire Stripping Length	0.55 in (14 mm) for bottom connection
Tightening Torque	30.98 lbf.in (3.5 N.m) bottom

Environment

Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution Degree	3 IEC 61009
Electromagnetic Compatibility	8/20 μs impulse withstand, 250 A EN/IEC 61009-1
Tropicalisation	2 IEC 60068-1
Relative Humidity	95 % 131 °F (55 °C)
Ambient Air Temperature For Operation	23140 °F (-560 °C)
Ambient Air Temperature For Storage	-40140 °F (-4060 °C)

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
Gtin	3606480684555
Returnability	No
Country Of Origin	US

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.43 in (8.7 cm)
Package 1 Width	4.72 in (12.0 cm)
Package 1 Length	5.83 in (14.8 cm)
Package 1 Weight	9.21 oz (261.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	15
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	9.68 lb(US) (4.39 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations