

Instantaneous auxiliary contact blocks (continued)

Lateral mounting



Number contacts	Combinations with basic contactor 10E	Contacts in acc. with EN 50012	Contacts in acc.with EN 50005	Aux.contacts •3 •4 •1 •2		Cat. no.	Ref. no.	Pack
• One or two additional blocks, to cover combinations of 1 or 2 contacts without increasing the height of the basic unit contactor								
Screw terminal								
1	20	10		1	0	MACL110AT	100560	10
1	11E	01		0	1	MACL101AT	100561	10
Ring terminal								
1	20	10		1	0	MACL110AR	103555	10
1	11E	01		0	1	MACL101AR	103556	10
Terminal: faston 2x2.8 insulated ⁽¹⁾								
1	20	10		1	0	MACL110AF	100562	10
1	11E	01		0	1	MACL101AF	100563	10
Terminal: printed circuit								
1	20	10		1	0	MACL110AI	100564	10
1	11E	01		0	1	MACL101AI	100565	10
• One or two additional blocks, when up to 6 or 7 contacts are needed (combination possible with frontal blocks) • One or two additional blocks on both sides, to cover up to five contacts (combination possible only with lateral blocks)								
Screw terminal								
1			10	1	0	MARL110ATS	100519	10
1			01	0	1	MARL101ATS	100520	10
Ring terminal								
1			10	1	0	MARL110ARS	103299	10
1			01	0	1	MARL101ARS	103298	10
Terminal: faston 2x2.8 insulated ⁽¹⁾								
1			10	1	0	MARL110AFS	100521	10
1			01	0	1	MARL101AFS	100522	10
Terminal: printed circuit								
1			10	1	0	MARL110AIS	100523	10
1			01	0	1	MARL101AIS	100524	10

(1) Terminal with wire 1mm²: Ie = 10A
Insulated terminal type B 2.8x0.8 with wire 1mm²: Ie = 8A, in accordance with DIN 46247