

VL Molded Case Circuit Breakers

Operating Mechanisms

Selection

Description	For MG Frame 800 A		For NG Frame 1200 A		For PG Frame 1600 A	
	Catalog Number	List Price \$	Catalog Number	List Price \$	Catalog Number	List Price \$
Max-Flex™, Variable Depth Flange Mounted Operator Kit Complete kit, includes plastic handle, breaker operator, and cable. NEMA 1, 3R, 12 For DG and FG operators, the cable is 36", all others are 48"	MFKM3R		MFKP3RS		MFKP3RS	
Handle Only, for Max-Flex™ Variable Depth NEMA 1, 3R, 12 Plastic NEMA 1, 3R, 12 Steel - epoxy coated NEMA 4, 4X Steel - chrome plated Solid color (all gray) Plastic ^① NEMA 1, 3R, 12 Solid color (black handle) Steel epoxy coated ^① NEMA 1, 3R, 12	MFHM3R MFHM3RS MFHM4X MFHM3RB MFHM3RSB		— MFHP3RS MFHP4X — MFHP3RSB	— —	— MFHP3RS MFHP4X — MFHP3RSB	— —
Breaker Operator Mechanism Only, for Max-Flex™	MFMM		MFMP		MFMP	
Cable Only, for Max-Flex™ Variable Depth 36" 48" 60" 72" 84" 96" 120" 144"	MFCM036 MFCM048 MFCM060 MFCM072 MFCM084 MFCM096 MFCM120 MFCM144		— MFCP048 MFCP060 MFCP072 MFCP084 MFCP096 MFCP120 MFCP144	— 	— MFCP048 MFCP060 MFCP072 MFCP084 MFCP096 MFCP120 MFCP144	—
Handle Auxiliary Switch Form C (1NO - 1NC), early break ^② 1 Aux. switch 2 Aux. switch	MFSPA1 MFSPA2		MFSPA1 MFSPA2		MFSPA1 MFSPA2	

CSO - Consult Sales Office for pricing.