

PRODUCT-DETAILS

MP1-40G-10

MP1-40G-10 Pushbutton



General Information

Extended Product Type	MP1-40G-10
Product ID	1SFA611100R4012
EAN	7320500261453
Catalog Description	MP1-40G-10 Pushbutton
Long Description	Modular Pushbutton - Momentary - Flush - Green - Non-illuminated - Black plastic - 1NO

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.048 m
Product Net Height	0.03 m

Product Net Depth / Length	0.062 m
Product Net Weight	0.034 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Green
Actuator Type	Flush
Bezel Material	Black Plastic
Illumination	Non-illuminated
Function	Momentary
Number of Auxiliary Contacts NO	1
Degree of Protection	Front IP66 Terminals IP20
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	690 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	Maximum 690 V
Rated Operational Current DC-13 (I _e)	(24 V) 5
Rated Operational Current AC-15 (I _e)	(220 / 240 V) 6 A
Power Loss	Maximum 2.5 W
Mechanical Durability	2 million
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm

Technical UL/CSA

Connecting Capacity UL/CSA	1x 18...14 AWG 2x 18...14 AWG
----------------------------	----------------------------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B

Business To Business

Certificates and Declarations (Document Number)

CQC Certificate	CQC2005010304154103 CQC2008010305274953
cULus Certificate	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001528 2020980305001106
Declaration of Conformity - CE	2CMT2015-005452
DNV GL Certificate	E-14107
Environmental Information	1SAC200079H0001
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005452

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.11 m
Package Level 1 Depth / Length	0.15 m
Package Level 1 Height	0.03 m
Package Level 1 Gross Weight	0.034 kg
Package Level 1 EAN	7320500261453

Classifications

Object Classification Code	S
ETIM 6	EC000221 - Front element for push button
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eClass	V11.0 : 27371228
UNSPSC	39121500
E-Number (Norway)	4372632
E-Number (Sweden)	3715052

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

