



PRODUCT-DETAILS

# NF80E-14

## NF80E-14 250-500V50/60HZ-DC Contactor Relay



General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | NF80E-14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Product ID            | 1SBH137001R1480                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| EAN                   | 3471523100343                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Catalog Description   | NF80E-14 250-500V50/60HZ-DC Contactor Relay                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Long Description      | NF contactor relays are used for switching auxiliary and control circuits. NF contactor relays include an electronic coil interface accepting a wide control voltage $U_c$ min. ... $U_c$ max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. NF contactor relays can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. NF contactor relays have built-in surge protection and do not require additional surge suppressors. - Poles: 8-pole contactor relays - Control Circuit: AC or DC operated - Accessories: a wide range of Accessories is available. |

Ordering

|                        |         |
|------------------------|---------|
| Minimum Order Quantity | 1 piece |
|------------------------|---------|

Popular Downloads

|                       |                 |
|-----------------------|-----------------|
| Data Sheet, Technical | 1SBC100214C0202 |
|-----------------------|-----------------|

Information

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101027M6801 |
| CAD Dimensional Drawing  | 2CDC001079B0201 |

Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 45 mm    |
| Product Net Depth / Length | 110.5 mm |
| Product Net Height         | 86 mm    |
| Product Net Weight         | 0.36 kg  |

Technical

|                                                             |                                                                                                                                                                                                                                                                        |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Auxiliary Contacts NO                             | 8                                                                                                                                                                                                                                                                      |
| Number of Auxiliary Contacts NC                             | 0                                                                                                                                                                                                                                                                      |
| Standards                                                   | IEC/EN 60947-1, IEC/EN 60947-5-1, UL 60335-2-40 LZGH2 A2L, UL 508, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 14-13                                                                                                                                             |
| Rated Operational Voltage                                   | Auxiliary Circuit 690 V                                                                                                                                                                                                                                                |
| Rated Frequency (f)                                         | Auxiliary Circuit 50 / 60 Hz<br>Control Circuit 50 / 60 Hz                                                                                                                                                                                                             |
| Conventional Free-air Thermal Current ( $I_{th}$ )          | acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A                                                                                                                                                                                                      |
| Rated Operational Current AC-15 ( $I_{\theta}$ )            | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A                                                                                                                                                                               |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | for 0.1 s 140 A<br>for 1 s 100 A                                                                                                                                                                                                                                       |
| Maximum Electrical Switching Frequency                      | (AC-15) 1200 cycles per hour<br>(DC-13) 900 cycles per hour                                                                                                                                                                                                            |
| Rated Operational Current DC-13 ( $I_{\theta}$ )            | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W                          |
| Rated Insulation Voltage ( $U_i$ )                          | acc. to IEC 60947-5-1 690 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                                                    |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 6 kV                                                                                                                                                                                                                                                                   |
| Maximum Mechanical Switching Frequency                      | 6000 cycles per hour                                                                                                                                                                                                                                                   |
| Rated Control Circuit Voltage ( $U_c$ )                     | 50 Hz 250 ... 500 V<br>60 Hz 250 ... 500 V<br>DC Operation 250 ... 500 V                                                                                                                                                                                               |
| Operate Time                                                | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms |
| Mounting on DIN Rail                                        | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                                                                                                                                                         |
| Mounting by Screws (not supplied)                           | 2 x M4 screws placed diagonally                                                                                                                                                                                                                                        |
| Connecting Capacity Auxiliary Circuit                       | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup>                            |

|                                        |                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Connecting Capacity<br>Control Circuit | Rigid Stranded 1/2x 1 ... 2.5 mm²                                                                                                 |
|                                        | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²                                                                                       |
|                                        | Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²                                                                               |
|                                        | Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²                                                                               |
|                                        | Rigid Solid 1/2x 1 ... 2.5 mm²                                                                                                    |
| Wire Stripping Length                  | Rigid Stranded 1/2x 1 ... 2.5 mm²                                                                                                 |
|                                        | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm                                                                                  |
| Degree of Protection                   | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 |
| Terminal Type                          | Screw Terminals                                                                                                                   |

Technical UL/CSA

|                             |                                                        |
|-----------------------------|--------------------------------------------------------|
| Connecting Capacity         | Rigid Solid 1/2x 18-14 AWG                             |
| Auxiliary Circuit UL/CSA    | Rigid Stranded 1/2x 18-14 AWG                          |
| Tightening Torque<br>UL/CSA | Auxiliary Circuit 11 in-lb<br>Control Circuit 11 in-lb |

Environmental

|                                               |                                                                                                                                                                                  |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                       | Close to Contactor for Storage -60 ... +80 °C<br>Near Contactor for Operation in Free Air -40 ... 70 °C                                                                          |
| Climatic Withstand                            | Category B according to IEC 60947-1 Annex Q                                                                                                                                      |
| Maximum Operating<br>Altitude Permissible     | Without Derating 3000 m                                                                                                                                                          |
| Resistance to Shock acc.<br>to IEC 60068-2-27 | Closed, Shock Direction: B1 25 g<br>Open, Shock Direction: B1 5 g<br>Shock Direction: A 30 g<br>Shock Direction: B2 15 g<br>Shock Direction: C1 25 g<br>Shock Direction: C2 25 g |
| Resistance to Vibrations                      | 4g Closed Position & 2g Open position 5 ... 300 Hz                                                                                                                               |

Material Compliance

|                                                   |                                                                        |
|---------------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                                 | 2CMT2021-006202                                                        |
| RoHS Information                                  | 2CMT2021-006277                                                        |
| RoHS Status                                       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control<br>Act - TSCA            | 2CMT2023-006525                                                        |
| WEEE B2C / B2B                                    | Business To Business                                                   |
| WEEE Category                                     | 5. Small Equipment (No External Dimension More Than 50 cm)             |

ABB EcoSolutions

|                                            |                 |
|--------------------------------------------|-----------------|
| Environmental Product<br>Declaration - EPD | 1SBD250584E3000 |
|--------------------------------------------|-----------------|

Certificates and Declarations

|                      |                                 |
|----------------------|---------------------------------|
| A2L Certificate - UL | 9AKK108469A4900;9AKK108469A4902 |
| ABS Certificate      | ABS_20-2060694-PDA              |
| BV Certificate       | BV_2634H24899C0                 |
| CB Certificate       | CB_SE-93051M2                   |
| CCC Certificate      | 2020980303000185                |
| CQC Certificate      | CQC2019010303267993             |

|                                     |                             |
|-------------------------------------|-----------------------------|
| Declaration of Conformity<br>- CCC  | CQC2011010303465426         |
| Declaration of Conformity<br>- CE   | 1SBD250005U1000             |
| Declaration of Conformity<br>- UKCA | 1SBD250036U1000             |
| DNV Certificate                     | DNV_TAE00001BV-5            |
| EAC Certificate                     | EAC_RU C-FR ME77 B03544     |
| GOST Certificate                    | GOST_POCCFR.ME77.B06804.pdf |
| LR Certificate                      | LRS_LR2003684TA-02          |
| RINA Certificate                    | RINA_ELE142224XG            |
| RMRS Certificate                    | RMRS_1802702280             |
| UL Certificate                      | UL_20180227_E252354_2_1     |
| UL Listing Card                     | UL_E252354                  |

Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 87 mm         |
| Package Level 1 Depth /<br>Length | 113 mm        |
| Package Level 1 Height            | 47 mm         |
| Package Level 1 Gross<br>Weight   | 0.36 kg       |
| Package Level 1 EAN               | 3471523100343 |
| Package Level 2 Units             | box 18 piece  |
| Package Level 2 Width             | 250 mm        |
| Package Level 2 Depth /<br>Length | 300 mm        |
| Package Level 2 Height            | 315 mm        |
| Package Level 2 Gross<br>Weight   | 12.96 kg      |
| Package Level 3 Units             | 864 piece     |

Classifications

|                                       |                                       |
|---------------------------------------|---------------------------------------|
| Object Classification Code            | K                                     |
| ETIM 7                                | EC000196 - Contactor relay            |
| ETIM 8                                | EC000196 - Contactor relay            |
| ETIM 9                                | EC000196 - Contactor relay            |
| eClass                                | V11.0 : 27371001                      |
| UNSPSC                                | 39121529                              |
| IDEA Granular Category<br>Code (IGCC) | 4763 >> Power contactor, DC switching |
| E-Number (Finland)                    | 3706451                               |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → NF Contactor Relays

