Product data sheet Characteristics

NSYMF1010

Microperforated mounting plate H1000xW1000 w/ holes diam 3,6mm on 12,5mm pitch





Main

Main		
Range	Spacial	
Accessory / separate part category	Mounting accessory	
Product or component type	Mounting plate	
Device application	Multi-purpose	
Enclosure nominal dimensions	1000 mm W: 1000 mm	
Mounting location	Direct fixing on backstuds Step slide	
Mounting plate description	Microperforated	
Range compatibility	Spacial CRN Spacial S3D Spacial S3X Thalassa PLM	
Quantity per set	Set of 1	
Material	Galvanised steel	
Complementary	Screwed on backstuds - screw type M8	
Fixing mode	By fixing element	
Fixing mode Maximum load	250 kg/m ² S3D, CRN, S3X enclosures 150 kg/m ² PLM enclosure	
Maximum load	250 kg/m ² S3D, CRN, S3X enclosures	
Maximum load Permanent permissible load	250 kg/m ² S3D, CRN, S3X enclosures 150 kg/m ² PLM enclosure 225.6 kg S3D, CRN, S3X enclosures	
Maximum load Permanent permissible load Height	250 kg/m² S3D, CRN, S3X enclosures 150 kg/m² PLM enclosure 225.6 kg S3D, CRN, S3X enclosures 135.4 kg PLM enclosure	
Maximum load Permanent permissible load Height Width	250 kg/m ² S3D, CRN, S3X enclosures 150 kg/m ² PLM enclosure 225.6 kg S3D, CRN, S3X enclosures 135.4 kg PLM enclosure 950 mm	
-	250 kg/m² S3D, CRN, S3X enclosures 150 kg/m² PLM enclosure 225.6 kg S3D, CRN, S3X enclosures 135.4 kg PLM enclosure 950 mm 950 mm	

Complementary

Fixing mode	Screwed on backstuds - screw type M8 By fixing element	6 2 2
Maximum load	250 kg/m² S3D, CRN, S3X enclosures 150 kg/m² PLM enclosure	
Permanent permissible load	225.6 kg S3D, CRN, S3X enclosures 135.4 kg PLM enclosure	
Height	950 mm	0
Width	950 mm	<u>د</u>
Surface and useful surface	90.3 dm ²	
Thickness	2.5 mm	
Product weight	17.1 kg	



Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period

18 months