

internal door for PLA enclosure H1500xW750 mm

NSYPAPLA157G

Main

Range	Thalassa
accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
mounting location	Front side
Range compatibility	Thalassa Thalassa PLA
Device composition	1 door fixing elements M8 brass inserts

Complementary

Material	Aluminium
Colour	Grey (RAL 7035)
lock type	Lock 5 mm double bar
Number of locks	2
Door type	Internal plain
Door opening side	Left (110 °)
Height	1398 mm
Width	648 mm
Depth	Available depth between enclosure door : 30 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	65.500 cm
Package 1 Length	141.000 cm
Package 1 Weight	7.800 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	12
Package 2 Height	90.000 cm

Package 2 Width	120.000 cm
Package 2 Length	200.000 cm
Package 2 Weight	249.000 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Image of product in real life situation



