

# internal door for PLA enclosure H750xW500 mm

NSYPAPLA75G

### Main

Range	Thalassa
accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
mounting location	Front side
Range compatibility	Thalassa Thalassa PLA
Device composition	1 door fixing elements M8 brass inserts

## Complementary

Material	Aluminium
Colour	Grey (RAL 7035)
lock type	Lock 5 mm double bar
Number of locks	2
Door type	Internal plain
Door opening side	Left (110 °)
Height	648 mm
Width	398 mm
Depth	Available depth between enclosure door : 30 mm

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	41.5 cm
Package 1 Length	66.0 cm
Package 1 Weight	2.96 kg

# Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Image of product in real life situation



