# **Product datasheet**

Specifications





Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 500x750x320mm, IP65, IK10

NSYPLA573G

#### Main

| Thalassa   |
|--|
| Thalassa PLA   |
| Multi-purpose  |
| Suitable enclosure   |
| PLA  |
| 500 mm   |
| 750 mm   |
| 320 mm   |
| Floor-standing   |
| 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door |
|  |

## Complementary

| Body type                   | Sealed top and bottom part assembled with side parts  |
|-----------------------------|---|
| Door type                   | Plain front   |
| Number of doors             | 1 door(s)   |
| Door opening side           | Reversible (120 °)  |
| Lock type                   | 2 points lock, 5 mm double-bar  |
| accessibility for operation | Rear<br>Front   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element  |
| Material                    | Polyester reinforced with fibreglass  |
| Colour                      | Grey (RAL 7035)   |
| Standards                   | IEC 62208<br>UL 508 A   |
| NEMA degree of protection   | NEMA 3<br>NEMA 2<br>NEMA 1<br>NEMA 5<br>NEMA 13<br>NEMA 3S<br>NEMA 12<br>NEMA 3R<br>NEMA 3X |

| product certifications      | DNV Marine<br>Veritas<br>UL/cUL listed |
|-----------------------------|--|
| Electrical insulation class | Class II                               |

## Environment

| IP degree of protection             | IP65 conforming to IEC 60529 (completely sealed) |
|-------------------------------------|--|
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door)        |
| Fire resistance                     | 960 °C conforming to IEC 62208                   |
| Ambient air temperature for storage | -3590 °C   |

## **Packing Units**

| Unit Type of Package 1       | PCE      |
|------------------------------|----------|
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 51.0 cm  |
| Package 1 Width              | 78.0 cm  |
| Package 1 Length             | 38.0 cm  |
| Package 1 Weight             | 18.22 kg |
| Unit Type of Package 2       | РАМ      |
| Number of Units in Package 2 | 9        |
| Package 2 Height             | 120 cm   |
| Package 2 Width              | 100 cm   |
| Package 2 Length             | 170 cm   |
| Package 2 Weight             | 166 kg   |

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information


#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |

### Product datasheet

#### **Technical Illustration**

#### Dimensions



## Product datasheet

Image of product in real life situation

