

Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, ventilated canopy, 1000x1250x420mm, IP44, IK10

NSYPLAT10124G

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2,241.87 USD

Main

| | |
|---------------------------|--|
| Range | Thalassa |
| Product name | Thalassa PLA |
| Enclosure type | Multi-purpose |
| Product or Component Type | Suitable enclosure |
| Version | PLAT |
| Nominal height | 39.4 in (1000 mm) |
| Nominal width | 49.2 in (1250 mm) |
| Nominal depth | 16.5 in (420 mm) |
| enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 2 door 2 rear panel 1 canopy |

Complementary

| | |
|-----------------------------|--|
| Body type | Open top and sealed bottom part assembled with side parts |
| Door type | Solid front |
| Number of doors | 2 |
| Door opening side | Right and left 120 °) |
| Lock type | 4 points lock, handle with 5 mm double bar insert |
| accessibility for operation | Front Top Rear |
| Removable parts | Door by hinges Rear panel by fixing element Canopy by fixing element |
| Material | polyester reinforced with fibreglass |
| color | Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | Veritas |
| Electrical Insulation Class | Class II |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| | |
|-------------------------------------|--|
| IP degree of protection | IP44 IEC 60529 with ventilated canopy) |
| IK degree of protection | IK10 IEC 62262 plain door) |
| Fire resistance | 1760 °F (960 °C) IEC 62208 |
| Ambient Air Temperature for Storage | -31...194 °F (-35...90 °C) |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10ES180034 |
| Discount Schedule | 0ES1 |
| GTIN | 3606480775185 |
| Returnability | No |
| Country of origin | ES |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 50.8 in (129.0 cm) |
| Package 1 Width | 39.4 in (100.0 cm) |
| Package 1 Length | 18.9 in (48.0 cm) |
| Package 1 Weight | 140.454 lb(US) (63.709 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 51.2 in (130 cm) |
| Package 2 Width | 39.4 in (100 cm) |
| Package 2 Length | 46.06 in (117 cm) |
| Package 2 Weight | 262.4 lb(US) (119 kg) |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations

Image of product in real life situation

