

# Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, open bottom, 1250x500x320mm, IP54, IK10

NSYPLAZ1253G

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 968.95 USD

## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Enclosure type            | Multi-purpose  |
| Product or Component Type | Suitable enclosure   |
| Version                   | PLAZ   |
| Nominal height            | 49.2 in (1250 mm)  |
| Nominal width             | 19.7 in (500 mm)   |
| Nominal depth             | 12.6 in (320 mm)   |
| enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door<br>1 plinth |

## Complementary

|                             |   |
|-----------------------------|---|
| Body type                   | Sealed top and open bottom part assembled with side parts |
| Door type                   | Solid front   |
| Number of doors             | 1   |
| Door opening side           | Reversible 120 °)   |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert         |
| accessibility for operation | Rear<br>Bottom<br>Front                                   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element            |
| Material                    | polyester reinforced with fibreglass                      |
| color                       | Gray RAL 7035)  |
| Standards                   | IEC 62208   |
| Product Certifications      | Veritas   |
| Electrical Insulation Class | Class II  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

|                                     |   |
|-------------------------------------|---|
| IP degree of protection             | IP54 IEC 60529 plinth type open bottom) |
| IK degree of protection             | IK10 IEC 62262 plain door)              |
| Fire resistance                     | 1760 °F (960 °C) IEC 62208              |
| Ambient Air Temperature for Storage | -31...194 °F (-35...90 °C)              |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10ES180034  |
| Discount Schedule | 0ES1          |
| GTIN              | 3606480775673 |
| Returnability     | No            |
| Country of origin | ES            |

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Number of Units in Package 1 | 1                         |
| Package 1 Height             | 50.8 in (129.0 cm)        |
| Package 1 Width              | 21.3 in (54.0 cm)         |
| Package 1 Length             | 15.0 in (38.0 cm)         |
| Package 1 Weight             | 65.938 lb(US) (29.909 kg) |
| Unit Type of Package 2       | PAM                       |
| Number of Units in Package 2 | 5                         |
| Package 2 Height             | 47.2 in (120 cm)          |
| Package 2 Width              | 39.4 in (100 cm)          |
| Package 2 Length             | 57.9 in (147 cm)          |
| Package 2 Weight             | 425.5 lb(US) (193 kg)     |

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

 Mercury Free

 RoHS Exemption Information   [Yes](#)

## Certifications & Standards

|                          |  |
|--------------------------|--|
| Reach Regulation         | <a href="#">REACH Declaration</a>  |
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)   |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile      | No need of specific recycling operations   |

Technical Illustration

Dimensions

---



Image of product in real life situation

