Product datasheet

Specifications

, Green Premium[™]



Floor standing polyester enclosure, Thalassa PLA, open bottom, ventilated canopy, 500x500x320mm, IP44, IK10

NSYPLAZT553G

() Discontinued

() Discontinued on: 1 Nov 2020

Main

| Thalassa |
|----------------------------------------------------------------------------------------------|
| Thalassa PLA |
| Multi-purpose |
| Suitable enclosure |
| PLAZT |
| 500 mm |
| 500 mm |
| 320 mm |
| Floor-standing |
| 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 canopy 1 plinth |
| |

Complementary

| • | |
|-----------------------------|----------------------------------------------------|
| Body type | Open top and bottom part assembled with side parts |
| Door type | Plain front |
| Number of doors | 1 door(s) |
| Door opening side | Reversible (180 °) |
| Lock type | 2 points handle lock, 5 mm double-bar |
| accessibility for operation | Front |
| | Rear |
| | Тор |
| | Bottom |
| Removable parts | Door by hinges |
| | Rear panel by fixing element |
| | Canopy by fixing element |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 |
| product certifications | Veritas |
| Electrical insulation class | Class II |
| | |

Life Is On Schneider

Environment

| IP degree of protection | IP44 conforming to IEC 60529 (with plinth type open bottom part and ventilated canopy) |
|-------------------------------------|----------------------------------------------------------------------------------------|
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance | 960 °C conforming to IEC 62208 |
| Ambient air temperature for storage | -3590 °C |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 56.0 cm |
| Package 1 Width | 54.0 cm |
| Package 1 Length | 38.0 cm |
| Package 1 Weight | 15.955 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 15 |
| Package 2 Height | 120 cm |
| Package 2 Width | 100 cm |
| Package 2 Length | 190 cm |
| Package 2 Weight | 249.325 kg |

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Product datasheet

Technical Illustration

Dimensions



Product datasheet

Image of product in real life situation

