Product data sheet

Specifications





Floor standing polyester enclosure, Thalassa PLA, open bottom, ventilated canopy, 750x500x420mm, IP44, IK10

NSYPLAZT754G

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 879.88 USD

Main

| Range | Thalassa |
|---------------------------|--|
| Product name | Thalassa PLA |
| Enclosure type | Multi-purpose |
| Product or Component Type | Suitable enclosure |
| Version | PLAZT |
| Nominal height | 29.5 in (750 mm) |
| Nominal width | 19.7 in (500 mm) |
| Nominal depth | 16.5 in (420 mm) |
| enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 canopy 1 plinth |

Complementary

| Body type | Open top and bottom part assembled with side parts |
|-----------------------------|--|
| Door type | Solid front |
| Number of doors | 1 |
| Door opening side | Reversible 180 °) |
| Lock type | 2 points handle lock, 5 mm double-bar |
| accessibility for operation | Front Top Bottom Rear |
| Removable parts | Door by hinges Rear panel by fixing element Canopy by fixing element |
| Material | polyester reinforced with fibreglass |
| color | Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | Veritas |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical Insulation Class Class II

Environment

| IP degree of protection | IP44 IEC 60529 with plinth type open bottom part and ventilated canopy) |
|-------------------------------------|---|
| IK degree of protection | IK10 IEC 62262 plain door) |
| Fire resistance | 1760 °F (960 °C) IEC 62208 |
| Ambient Air Temperature for Storage | -31194 °F (-3590 °C) |

Ordering and shipping details

| Category | US10ES180034 |
|-------------------|---------------|
| Discount Schedule | 0ES1 |
| GTIN | 3606480776328 |
| Returnability | No |
| Country of origin | ES |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 32.7 in (83.0 cm) |
| Package 1 Width | 21.3 in (54.0 cm) |
| Package 1 Length | 18.9 in (48.0 cm) |
| Package 1 Weight | 59.137 lb(US) (26.824 kg) |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 47.2 in (120 cm) |
| Package 2 Width | 39.4 in (100 cm) |
| Package 2 Length | 73.6 in (187 cm) |
| Package 2 Weight | 443.1 lb(US) (201 kg) |



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Technical Illustration

Dimensions



Image of product in real life situation



