Product datasheet

Specifications

Green Premium™

Polyester insulating mounting plate for PLA enclosure H1250xW750mm

NSYPMA127

⊘ Discontinued on: 01-Nov-2020

⊘ **Discontinued**

Main

Range	Thalassa
Accessory / Separate Part Categor	Mounting accessory
Product Or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure Nominal Dimensions	-
Mounting Location	Back inserts Step slide
Mounting Plate Description	Insulating
Range Compatibility	Thalassa Thalassa PLA
Device Composition	1 mounting plate
Material	Polyester
Colour	Grey (RAL 7035)

Complementary

Fixing Mode	By screws - screw type M8 - on back inserts location
Permanent Permissible Load	150 kg
Height	Nominal: 1250 mm Real: 1140 mm
Width	Nominal: 750 mm Real: 625 mm
Depth	Real : 125 mm
Thickness	5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.5 cm
Package 1 Width	62.5 cm
Package 1 Length	112.5 cm
Package 1 Weight	3.52 kg

Contractual warranty

Warranty 18 months

Life Is On | Schneider Electric

Sustainability ✿ Green Premium™

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations