# Product data sheet

Specifications





Wall mounted steel enclosure, Spacial S3DC, plain door, without plain chasis, 800x600x200mm, IP66, IK10

NSYS3DC8620

#### Main

| Range                       | Spacial                    |
|-----------------------------|----------------------------|
| Product Name                | Spacial S3DC               |
| Application                 | Multi-purpose              |
| Category                    | Compact enclosure          |
| Enclosure Nominal Height    | 800 mm                     |
| Enclosure Nominal Width     | 600 mm                     |
| Enclosure Nominal Depth     | 200 mm                     |
| Door Type                   | Plain                      |
| Mounting Plate Description  | Without mounting plate     |
| Type Of Gland Plate         | Without gland plate        |
| Installation Accessory Type | Wall-mounting              |
| Device Composition          | 1 body<br>1 door<br>1 lock |

## Complementary

| Body Type                   | Gutter-shaped front profile double sheet thickness<br>Single piece body |
|-----------------------------|---|
| Number Of Doors             | Front face: 1 door(s)   |
| Door Opening Side           | Reversible (120 °)  |
| Lock Type                   | 3 points lock, screw driver insert                                      |
| Accessibility For Operation | Front   |
| Removable Parts             | Door by hinges  |
| Material                    | Steel   |
| Surface Finish              | Epoxy-polyester powder  |
| Colour                      | Grey (RAL 7035)   |
| Standards                   | IEC 62208   |
| Product Certifications      | UL  |
| Net Weight                  | 19.8 kg   |

# Environment

| Nema Degree Of Protection | NEMA 4X/13                   |
|---------------------------|------------------------------|
| Ik Degree Of Protection   | IK10 conforming to IEC 62262 |

Ip Degree Of Protection

IP66 conforming to IEC 60529

# **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 26 cm   |
| Package 1 Width              | 63 cm   |
| Package 1 Length             | 89 cm   |
| Package 1 Weight             | 19.8 kg |
| Unit Type Of Package 2       | РАМ     |
| Number Of Units In Package 2 | 15      |
| Package 2 Height             | 200 cm  |
| Package 2 Width              | 100 cm  |
| Package 2 Length             | 120 cm  |
| Package 2 Weight             | 312 kg  |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Mercury Free

Rohs Exemption Information

## **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |