# **Product datasheet**

Specification





# Spacial SM compact enclosure without mounting plate - 2000x1000x400 mm

NSYSM2010402D

#### Main

| Range                       | PanelSeT   |
|-----------------------------|--|
| Product name                | PanelSeT SM  |
| Product or component type   | Compact enclosure  |
| Application                 | Multi-purpose  |
| Installation accessory type | Floor-standing   |
| Device composition          | body     door     cable gland plate     locking system with handle: door     blocking system: left door     mounting plate bracket |
| Removable parts             | Door by screws hinge<br>Mounting plate bracket by screws   |
| Enclosure nominal height    | 2000 mm  |
| Enclosure nominal width     | 1000 mm  |
| Enclosure nominal depth     | 400 mm   |

## Complementary

| Number of doors             | Front: 2 door(s)  |
|-----------------------------|---|
| Door opening side           | Left (120 °)<br>Right (120 °)   |
| Door type                   | Plain   |
| lock type                   | 4 points lock, handle with 5 mm double bar insert   |
| Body type                   | Front part forming a rigid frame with welded corners Single piece body with welded rear panel |
| Mounting plate description  | Without mounting plate  |
| Type of gland plate         | Standard  |
| Cable entry                 | 1 entry   |
| Material                    | Body: sheet steel Door: sheet steel Hinge: zamak  |
| Surface finish              | Epoxy-polyester powder  |
| Colour                      | Enclosure: grey (RAL 7035)<br>Handle: black (RAL 9005)  |
| accessibility for operation | Front   |
| Net weight                  | 115 kg  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## **Environment**

| Standards               | IEC 62208                    |
|-------------------------|------------------------------|
| Product certifications  | BV<br>DNV<br>UL              |
| IK degree of protection | IK10 conforming to IEC 62262 |
| IP degree of protection | IP55 conforming to IEC 60529 |

# **Packing Units**

| •                            |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 213.0 cm |
| Package 1 Width              | 104.5 cm |
| Package 1 Length             | 49.0 cm  |
| Package 1 Weight             | 115.0 kg |
| Unit Type of Package 2       | PAL      |
| Number of Units in Package 2 | 2        |
| Package 2 Height             | 98 cm    |
| Package 2 Width              | 105 cm   |
| Package 2 Length             | 213 cm   |
| Package 2 Weight             | 220 kg   |

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |