NSYSMX181640H

SMX 316L stainless monobloc enclosure, H1800xW1600xD400mm, Scotch Brite® finish.

Green Premium Product

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	Spacial
Product name	Spacial SMX
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	70.87 in (1800 mm)
Nominal width	62.99 in (1600 mm)
Nominal depth	15.75 in (400 mm)
Product installation	Floor-standing
Device composition	1 body 2 door 1 cable gland plate 1 locking system with handle door 4 mounting plate bracket

Complementary

Body type	Single piece body folded and welded
Door type	Plain
Number of doors	Front face 2
Door opening side	Reversible 120 °)
Lock type	3 points lock, handle with 5 mm double-bar insert
Mounting plate description	Without mounting plate
Type of gland plate	Plain
Accessibility for operation	Front
Removable parts	Door by hinges Mounting plate bracket by screws Cable gland plate by clips
Material	Handle zamak Hinge stainless steel Body and door stainless steel 316L
Surface finish	Enclosure Scotch-Brite® brushed Handle painted
Thickness	0.06 in (1.5 mm)
Product weight	335.10 lb(US) (152 kg)

Environment

Standards	IEC 62208
Product certifications	UL 508 CAN/CSA 22
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK10 IEC 62262
Environmental characteristic	Corrosive Specific hygiene

Ordering and shipping details

Category	80035 - ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	03606480155789
Package weight(Lbs)	151.68 kg (334.4 lb(US))
Returnability	No
Country of origin	BG

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric