OC10G06PNBN00NSO32



OC10G06PNBN00NSO32 Cam switch



__

General Information

| Extended Product Type | OC10G06PNBN00NSO32 |
|-----------------------|---|
| Product ID | 1SCA126565R1001 |
| EAN | 6417019565354 |
| Catalog Description | OC10G06PNBN00NSO32 Cam switch |
| Long Description | OC10 Cam switch, lth=10A, Multi-Step, 6-contacts, Snap-on door mounting, Black Basic handle. Black handle and frontplate with standard text are included. Special engraved frontplates to be ordered as separate items. |

_

Ordering

| Minimum Order Quantity | 1 piece |
|------------------------|----------|
| Customs Tariff Number | 85365080 |

Popular Downloads

| Data Sheet, Technical Information | 1SCC302009C0201 |
|-----------------------------------|-----------------|
| Instructions and Manuals | 1SCC302013F0006 |
| Wiring Diagram | 1SCC302014M0201 |

Dimensions

| Product Net Width | 32 mm | |
|----------------------------|---------|--|
| Product Net Height | 32 mm | |
| Product Net Depth / Length | 93 mm | |
| Product Net Weight | 0.06 kg | |

_

Technical

| Rated Operational Current AC-22A (I _e) | (500 V) 10 A |
|--|--|
| Rated Operational Current AC-23A (I _e) | (230 V) Single Phase 7.2 A (400 V) Single Phase 6.1 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A |
| Rated Operational Power AC-23A (P _e) | (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 10 A |
| Conventional Thermal Current (I _{the}) | Fully Enclosed 10 A |

| Rated Continuous Thermal Current | 10 A |
|---|--|
| Rated Impulse Withstand Voltage (U_{imp}) | 2.5 kV |
| Rated Insulation Voltage (U _i) | 500 V |
| Rated Operational Voltage | 500 V |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 0.12 kA for 3 s 0.07 kA |
| Power Loss | 0.6 W |
| Pollution Degree | 3 |
| Handle Type | Basic handle |
| Special Functions | Multistep switch: 3-step, with 0-position: 12 o'clock, step angle 30°, front plate 0-1-2-3 |
| Color | Black |
| Mounting Type | Snap-on door mounting |
| Number of Contacts | 6 |
| Number of Poles | 2 |
| Terminal Type | Screw Terminals |

_

Technical UL/CSA

Certificates and Declarations (Document Number)

| Declaration of Conformity - CE | 1SCC302005D0201 |
|--------------------------------|-----------------|
| Instructions and Manuals | 1SCC302013F0006 |

__

Container Information

| Package Level 1 Units | 1 piece |
|--------------------------------|---------------|
| Package Level 1 Width | 50 mm |
| Package Level 1 Depth / Length | 108 mm |
| Package Level 1 Height | 50 mm |
| Package Level 1 Gross Weight | 0.06 kg |
| Package Level 1 EAN | 6417019565354 |

Classifications

| Object Classification Code | Q |
|----------------------------|--|
| ETIM 5 | EC002611 - Control switch |
| ETIM 6 | EC002611 - Control switch |
| ETIM 7 | EC002611 - Control switch |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

_

Categories