


400A – 800A UL fuse class J, T, L

Disconnect
switches
Fusible

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft
- 1 terminal lug kit



OES400J3



OXP12X280




OHB145J12




OZXA-26

200 – 800 Amp switches, 600V

UL general purpose amp rating	UL Fuse type 600V	Maximum horsepower rating					Catalog number	List price
		Three phase						
		200V	208V	240V	480V	600V		
2 pole								
400	J	—	—	—	—	—	OES400J2	
600	J	—	—	—	—	—	OES600J2	
800	L	—	—	—	—	—	OES800L2	
3 pole								
400	J	100	125	125	250	350	OES400J3	
600	J	150	150	200	400	500	OES600J3	
800	L	200	200	250	500	600	OES800L3	
4 pole								
400	J	100	125	125	250	350	OES400J4	
600	J	150	150	200	400	500	OES600J4	
800	L	200	200	250	500	600	OES800L4	



OES400J3




OES600J3
OES800L3



OHB_J12



OHY_J12



YASDA-33

Pistol handles — □ .47 x .47" (□ 12 x 12mm)

UL/NEMA type	IEC type	Color	Length inches/mm	Marking	Defeat- able	Padlock- able	Weight (lbs)	Catalog number	List price
1,3R,12	IP65	Black	4.9/125	O/I & Off/On	Yes	Yes	0.39	OHB125J12	
1,3R,12	IP65	Red/Yel	4.9/125	O/I & Off/On	Yes	Yes	0.39	OHY125J12	
1,3R,12	IP65	Black	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHB145J12	
1,3R,12	IP65	Red/Yel	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHY145J12	
1,3R,12	IP65	Black	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHB175J12	
1,3R,12	IP65	Red/Yel	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHY175J12	
1,3R,4,4X,12	IP65	Black	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHB145L12	
1,3R,4,4X,12	IP65	Red/Yel	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHY145L12	
1,3R,4,4X,12	IP65	Black	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHB175L12	
1,3R,4,4X,12	IP65	Red/Yel	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHY175L12	
1,3R,4,4X,12	IP65	Metal	8.7/220	Off/On	—	Yes	1.50	YASDA-8	

Direct mount handles

Item	Weight (lbs)	Catalog number	List price
Mounts to 12mm shaft	0.78	YASDA-33	