




ON-OFF Switches




O_A1_




O_A2_




O_A3_



O_A4_



O_A5_



O_A6_

Black handle and front plate with standard text are included. The type and the ordering number are for one piece.
Special engraved front-plates to be ordered as separate items.

Function	Number of poles	Rated thermal current [A]	Weight [kg]	Catalog number
----------	-----------------	---------------------------	-------------	----------------

Rotating angle 90°, O-position: 9 o'clock

Miniature, door mounted

0 - 1	1	10	0.04	OMA1PB
	2	10	0.04	OMA2PB
	3	10	0.05	OMA3PB
0 - 1	4	10	0.05	OMA4PB
	5	10	0.06	OMA5PB
	6	10	0.06	OMA6PB

Normal, door mounted

0 - 1	1	25	0.08	ONA1PB
	2	25	0.09	ONA2PB
	3	25	0.10	ONA3PB
0 - 1	4	25	0.11	ONA4PB
	5	25	0.12	ONA5PB
	6	25	0.12	ONA6PB

Large, door mounted

0 - 1	1	40	0.13	OL40A1PB
	2	40	0.17	OL40A2PB
	3	40	0.21	OL40A3PB
0 - 1	4	40	0.25	OL40A4PB
	5	40	0.29	OL40A5PB
	6	40	0.33	OL40A6PB

Modular, DIN-rail mounted

0 - 1	1	25	0.09	ONA1M
	2	25	0.10	ONA2M
	3	25	0.11	ONA3M
	6	25	0.12	ONA6M

Key operated, withdrawable in both positions, rotating angle 90°, O-position: 9 o'clock ①

Miniature, door mounted

0 - 1	1	10	0.06	OMA1KB
	3	10	0.07	OMA3KB

Normal, door mounted 90°

0 - 1	1	25	0.11	ONA1KB
	3	25	0.13	ONA3KB

Packing sizes: OM 130 x 100 x 120 [mm]
ON, OL 250 x 100 x 110 [mm]

① Different withdrawability of key is also possible to be ordered as special switch.

Standard delivery with black handle. Available also as an optional extra with grey handle, please change in type designation B to G, eg. OMA1PB would be OMA1PG with grey handle.