



PRODUCT-DETAILS

# OS30FAJF30

## OS30FAJF30 FUSIBLE DISCONNECT SW



| General Information   |                                  |
|-----------------------|----------------------------------|
| Extended Product Type | OS30FAJF30                       |
| Product ID            | 1SCD000025R0014                  |
| Catalog Description   | OS30FAJF30 FUSIBLE DISCONNECT SW |
| Long Description      | 3P FUS SW 30A J FLANGE OPER.     |

| Material Compliance                         |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                           | 1SCC011021D0201                                                        |
| RoHS Information                            | 1SCC011020D0201                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 1SCC011025D0201                                                        |

### Popular Downloads

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SCC311013C0201                    |
| Instructions and Manuals          | No Instructions and Manuals needed |

Ordering

|                        |                    |
|------------------------|--------------------|
| Minimum Order Quantity | 1 piece            |
| Customs Tariff Number  | 8536509065         |
| Country of Origin      | United States (US) |

Technical

|                           |                                                                              |
|---------------------------|------------------------------------------------------------------------------|
| Connecting Capacity       | Stranded 0.75 ... 10 mm <sup>2</sup><br>Flexible 0.75 ... 10 mm <sup>2</sup> |
| Rated Operational Voltage | Main Circuit 690 V AC                                                        |

Technical UL/CSA

|               |      |
|---------------|------|
| Ampere Rating | 30 A |
|---------------|------|

Certificates and Declarations

|                                |                         |
|--------------------------------|-------------------------|
| ATEX Certificate               | No certification needed |
| Declaration of Conformity - CE | No declaration needed   |

External Classifications and Standards

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 8        | EC001040 - Fuse switch disconnecter                        |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

