



PRODUCT-DETAILS

OS30FAJS30

OS30FAJS30 FUSIBLE DISCONNECT SWITCH



General Information	
Extended Product Type	OS30FAJS30
Product ID	1SCA108834R1001
EAN	6417019421070
Catalog Description	OS30FAJS30 FUSIBLE DISCONNECT SWITCH
Long Description	Switch Fuses,Side operated,3-pole,30 (Right Side),Class J,30 A,Handle and shaft not included,

ABB EcoSolutions	
Environmental Product Declaration - EPD	1SCC311204D0201

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201

RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311030M0202
Mechanical Drawings	stp_os30fajs30.stp
Environmental Product Declaration - EPD	1SCC311204D0201

Environmental

Pollution Degree	3
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Lithuania (LT)

Dimensions

Product Net Width	234 mm
Product Net Height	130 mm
Product Net Depth / Length	130 mm
Product Net Weight	0.71 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	234 mm
Package Level 1 Height	130 mm
Package Level 1 Gross Weight	0.82 kg
Package Level 1 EAN	6417019421070

Technical

Cable Cross-Section	2.5 ... 25 mm ²
Connecting Capacity	Stranded 0.75 ... 10 mm ² Flexible 0.75 ... 10 mm ²
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 32 A
Conventional Thermal Current (I _{the})	Fully Enclosed 32 A

Fuse Size	30 A
Fuse System	Class J
Handle Type	Handle and shaft not included
Mounting Type	Base mounting
Number of Poles	3P
Operating Mode	Side Operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 2 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Rated Current (I_n)	Main Circuit 30 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21A (I_e)	(500 V) 30 A (690 V) 30 A
Rated Operational Current AC-22A (I_e)	(500 V) 30 A (690 V) 30 A
Rated Operational Current AC-23A (I_e)	(500 V) 30 A (690 V) 30 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 7.5 kW (400 V) 15 kW (415 V) 15 kW (500 V) 18.5 kW (690 V) 22 kW
Rated Operational Voltage	Main Circuit 600 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 1 kiloampere rms
Standards	UL98 IEC 60947-3
Switches Operating Mechanism	30 (Right Side)
Terminal Type	Screw Terminals
Tightening Torque	1.5 ... 2 N·m
Wire Stripping Length	Main Circuit 12 ... 14 mm Main Circuit 0.47 ... 0.55 in

Technical UL/CSA

Ampere Rating	30 A
Horsepower Rating UL/CSA	(acc. to UL 240 V) 7.5 Hp (acc. to UL 480 V) 15 Hp (acc. to UL 600 V) 20 Hp
Wire Stripping Length	Main Circuit 12 ... 14 mm Main Circuit 0.47 ... 0.55 in
Tightening Torque	1.5 ... 2 N·m
Tightening Torque UL/CSA	Wire-Clamp 17 in·lb

Certificates and Declarations

ATEX Certificate	No certification needed
------------------	-------------------------

Declaration of Conformity - CE	1SCC311129D2702
DNV GL Certificate	1SCC311125D0203
UL Certificate	CULUS CERTIFICATE OS30FA_

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC001040 - Fuse switch disconnecter
ETIM 9	EC001040 - Fuse switch disconnecter
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnecter
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

