



PRODUCT-DETAILS

OT1000E04

OT1000E04 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT1000E04
Product ID	1SCA022860R6070
EAN	6417019309316
Catalog Description	OT1000E04 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-d disconnector, handle and shaft are not included, terminal bolt kit included

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC301120M0201
Environmental Information	1SCC301233D0201
Environmental Product Declaration - EPD	1SCC301300D0201

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301047M0213
Mechanical Drawings	1SCC301494F0001 1SCC301493F0001 OT1250E04.igs
Environmental Product Declaration - EPD	1SCC301300D0201

Environmental

Degree of Protection	Front IP00
Environmental Information	1SCC301233D0201
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	414.5 mm
Product Net Height	306 mm
Product Net Depth / Length	145.5 mm
Product Net Weight	18.8 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	400 mm
Package Level 1 Depth / Length	435 mm
Package Level 1 Height	170 mm
Package Level 1 Gross Weight	20.1 kg
Package Level 1 EAN	6417019309316

Technical

Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ °C } 1000\text{ A}$
Conventional Thermal Current (I_{the})	Fully Enclosed 1000 A
Degree of Protection	Front IP00
Distance Between Phases	Standard
Fourth Pole Position	Right Side

Fourth Pole Type	Switched - Simultaneous Function
Handle Type	Handle and shaft not included
Lock Type	No
Mechanical Durability	6000
Mounting Type	Base mounting
Number of Poles	4P
Operating Mode	Front operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 19 W
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P _e)	(400 ... 415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 92 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 50 kA
Special Functions	No
Standards	IEC 60947-3
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
-------------------	--------------------------------

Certificates and Declarations

A2L Certificate - IEC	1SCC301338D0201
Declaration of Conformity - CE	1SCC301155D2704
DNV GL Certificate	1SCC301184D0203

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
eClass	V11.1 : 27371403

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3661614

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

