



PRODUCT-DETAILS

OT2000U03

OT2000U03 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT2000U03
Product ID	1SCA117313R1001
EAN	6417019493336
Catalog Description	OT2000U03 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted non-fusible diconnect switch, handle and shaft are not included, terminal bolt kit included

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC301120M0201
Environmental Product Declaration - EPD	1SCC301300D0201

Material Compliance	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)		
REACH Declaration		1SCC011021D0201
RoHS Information		1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Toxic Substances Control Act - TSCA		1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information		1SCC301020C0201
Instructions and Manuals		1SCC301094M0203
Mechanical Drawings	1SCC307548F0201OT1600-2000U03.igs	
Environmental Product Declaration - EPD		1SCC301300D0201

Environmental

Degree of Protection	Front IP00
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	490 mm
Product Net Height	546 mm
Product Net Depth / Length	415 mm
Product Net Weight	53.7 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	420 mm
Package Level 1 Depth / Length	550 mm
Package Level 1 Height	490 mm
Package Level 1 Gross Weight	56.3 kg
Package Level 1 EAN	6417019493336

Technical

Degree of Protection	Front IP00
Distance Between Phases	Standard

Handle Type	Handle and shaft not included
Lock Type	No
Mechanical Durability	2500
Mounting Type	Base mounting
Number of Poles	3P
Operating Mode	Front operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 96 W
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA
Special Functions	No
Standards	UL 98 / CSA C22.2 NO.4
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 56 N·m

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	2000 A
Tightening Torque	acc. IEC 60947-1 56 N·m
Tightening Torque UL/CSA	500 in·lb

Certificates and Declarations

ATEX Certificate	No certification needed
cUL Certificate	cULus certificate OT1600-2000
Declaration of Conformity - CE	No declaration needed
UL Certificate	cULus certificate OT1600-2000
VDE Certificate	No certification needed

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

