



PRODUCT-DETAILS

# OT400E12YP

## OT400E12YP BY-PASS SWITCH



General Information	
Extended Product Type	OT400E12YP
Product ID	1SCA123584R1001
EAN	6417019543680
Catalog Description	OT400E12YP BY-PASS SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

Environmental

Degree of Protection	Front IP20
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	240 mm 9.45 in
Product Net Height	185 mm 7.28 in
Product Net Depth / Length	306 mm 12.05 in
Product Net Weight	11.51 kg 25.38 lb

Container Information

Package Level 1 Units	box 1 box
Package Level 1 Width	265 mm 10.43 in
Package Level 1 Depth / Length	375 mm 14.76 in
Package Level 1 Height	330 mm 12.99 in
Package Level 1 Gross Weight	11.93 kg 26.3 lb
Package Level 1 EAN	6417019543680

Technical

Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 400 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Degree of Protection	Front IP20
Distance Between Phases	Standard
Handle Color	Black
Handle Type	Handle and shaft included
Mounting Type	Base mounting

Number of Poles	3P
Operating Mode	Front operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 10 W
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 15 kiloampere rms
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m
Transition Type	Open

## Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m
-------------------	--------------------------------

## Certificates and Declarations

Declaration of Conformity - CE	1SCC301195D2703
--------------------------------	-----------------

## External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122217
IDEA Granular Category Code (IGCC)	5214 >> Rotary switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Bypass Switches

