



PRODUCT-DETAILS

OT400U02
OT400U02 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT400U02
Product ID	1SCA022748R1140
EAN	6417019242804
Catalog Description	OT400U02 SWITCH-DISCONNECTOR
Long Description	Handle and shaft must be ordered separately.

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC301118M0201
Environmental Information	1SCC301266D0201
Environmental Product Declaration - EPD	1SCC301283D0201

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301035M0019
Mechanical Drawings	1SCC301260F0002 1SCC301259F0002 OT315-400U02.stp OT315-400U02.igs
Environmental Product Declaration - EPD	1SCC301283D0201

Environmental

Degree of Protection	Front IP00
Environmental Information	1SCC301266D0201
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	167 mm
Product Net Height	220 mm
Product Net Depth / Length	105 mm
Product Net Weight	2.3 kg 5.1 lb

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm 9.8 in
Package Level 1 Depth / Length	290 mm 11.4 in
Package Level 1 Height	170 mm 6.7 in
Package Level 1 Gross Weight	2.6 kg 5.8 lb

Package Level 1 EAN

6417019242804

Technical	
Conventional Thermal Current (I _{the})	Fully Enclosed 400 A
Degree of Protection	Front IP00
Distance Between Phases	Standard
Handle Type	Handle and shaft not included
Lock Type	No
Mechanical Durability	16000
Mounting Type	Base mounting
Number of Poles	2P
Operating Mode	Front operated
Pollution Degree	3
Power Loss	at Rated Operating Conditions per Pole 10 W
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 65 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 15 kA
Special Functions	No
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Switches Operating Mechanism	Mechanism at the End of the Switch 02 (Left Side)
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 42.4 N·m

Technical UL/CSA	
Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	400 A
Tightening Torque	acc. IEC 60947-1 42.4 N·m

Certificates and Declarations	
Declaration of Conformity - CE	1SCC301135D2704
UL Certificate	cULus certificate OT200-400

External Classifications and Standards	
Object Classification	Q

Code	
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

