

PRODUCT-DETAILS

## OT400U03C

## OT400U03C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT400U03C
Product ID	1SCA022771R2990
EAN	6417019251714
Catalog Description	OT400U03C CHANGE-OVER SWITCH
Long Description	Handle and shaft has to be ordered separately

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0201

Dimensions	
Product Net Width	251 mm
Product Net Height	185 mm

Product Net Depth /	203 mm
Length	
Product Net Weight	5.46 kg
	12.04 lb

Technical	
Rated Operational	(380 415 V) 400 A
Current AC-21A (I <sub>e</sub> )	(500 V) 400 A (690 V) 400 A
Rated Operational	(380 415 V) 400 A
Current AC-22A (I <sub>e</sub> )	(500 V) 400 A (690 V) 400 A
Rated Operational	(380 415 V) 400 A
Current AC-23A (I <sub>e</sub> )	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B (I <sub>e</sub> )	(380 415 V) 400 A
Rated Operational Current AC-33B (I <sub>e</sub> )	(380 415 V) 400 A
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 400 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 15 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 10 W
Pollution Degree	
Handle Color	Black
Handle Type	Handle and shaft not included
	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Mechanical Durability	8000 cycle
Transition Type	Open

Technical UL/CSA	
Horsepower Rating	(acc. to UL 240 V) 125 Hp
UL/CSA	(acc. to UL 480 V) 250 Hp
	(acc. to UL 600 V) 350 Hp
Ampere Rating UL/CSA	400 A

Environmental	
Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303007D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0201
RoHS Information	1SCC301149D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm 9.45 in
Package Level 1 Depth / Length	270 mm 10.63 in
Package Level 1 Height	218 mm 8.58 in
Package Level 1 Gross Weight	5.87 kg 12.94 lb
Package Level 1 EAN	6417019251714

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

