



PRODUCT-DETAILS

OT400U04C
OT400U04C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT400U04C
Product ID	1SCA022771R2210
EAN	6417019251646
Catalog Description	OT400U04C CHANGE-OVER SWITCH
Long Description	400A, 4 pole manual change-over switch. Handle and shaft has to be ordered separately. UL version.

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC303051M0201
Environmental Information	1SCC303050D0201

Material Compliance	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0208

Environmental

Degree of Protection	Front IP20
Environmental Information	1SCC303050D0201
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	305 mm 12.01 in
Product Net Height	185 mm 7.28 in
Product Net Depth / Length	203 mm 7.99 in
Product Net Weight	7.66 kg 16.89 lb

Container Information

Package Level 1 Units	box 1 box
Package Level 1 Width	240 mm 9.45 in
Package Level 1 Depth / Length	325 mm 12.8 in
Package Level 1 Height	218 mm 8.58 in
Package Level 1 Gross Weight	8.11 kg 17.88 lb
Package Level 1 EAN	6417019251646

Technical

Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 400 A
--	-----------------

Degree of Protection	Front IP20
Distance Between Phases	Standard
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Handle Color	Black
Handle Type	Handle and shaft not included
Mechanical Durability	8000 cycle
Mounting Type	Base mounting
Number of Poles	4P
Operating Mode	Front operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 10 W
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B (I _e)	(380 ... 415 V) 400 A
Rated Operational Current AC-33B (I _e)	(380 ... 415 V) 400 A
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 15 kiloampere rms
Standards	UL 98 / IEC60947-6-1
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m
Transition Type	Open

Technical UL/CSA

Ampere Rating	400 A
Horsepower Rating UL/CSA	(acc. to UL 240 V) 125 Hp (acc. to UL 480 V) 250 Hp (acc. to UL 600 V) 350 Hp
Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m

Certificates and Declarations

Declaration of Conformity - CE	1SCC303004D2703
DNV Certificate	1SCC303138D0201

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnect
ETIM 9	EC000216 - Switch disconnect (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

