

PRODUCT-DETAILS

## **OT400U12-1000** OT400U12-1000 SWITCH-DISCONNECTOR



Extended Product Type	OT400U12-1000
Product ID	1SCA159826R1001
EAN	6417019893266
Catalog Description	OT400U12-1000 SWITCH-DISCONNECTOR
Long Description	Base mounting 3-pole, front operated UL98 switch-disconnector for up to 1000VAC, handle and shaft not included, lug terminal , bolt kit included

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC301118M0201
Environmental Information	1SCC301266D0201
Environmental Product Declaration - EPD	1SCC301283D0201

Material Compliance	9AKK108467A5658
Reporting Template (CMRT)	
REACH Declaration	1SCC011021D020
RoHS Information	1SCC011020D020
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
Toxic Substances Control Act - TSCA	1SCC011025D020
Popular Downloads	
Data Sheet, Technical Information	No documentation needed
Instructions and Manuals	1SCC301035M0019
Mechanical Drawings	1SCC301268F0002;1SCC301267F0002
Environmental Product Declaration - EPD	1SCC301283D0201
Environmental	
	10000000
Environmental Information Ordering	1SCC301266D0201
Information	1 piece 85365080
Information <b>Ordering</b> Minimum Order Quantity Customs Tariff Number Country of Origin	1 piece 85365080
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions	1 piece 8536508( Finland (Fl
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width	1 pieco 85365080 Finland (Fl 226 mn
Information Ordering Minimum Order Quantity Customs Tariff Number	1 piece 85365080 Finland (Fi 226 mm 220 mm
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width Product Net Height Product Net Depth /	1 piece 85365080 Finland (Fl) 226 mm 220 mm 105 mm
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width Product Net Height Product Net Depth / Length	1 piece 85365080 Finland (Fi) 226 mm 220 mm 105 mm 3.0 kg
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight	1 piece 85365080 Finland (Fi 226 mm 220 mm 105 mm 3.0 kg
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Container Information Package Level 1 Units	1 piece 85365080 Finland (Fl) 226 mm 220 mm 105 mm
Information  Ordering  Minimum Order Quantity  Customs Tariff Number  Country of Origin  Dimensions  Product Net Width  Product Net Height  Product Net Depth / Length  Product Net Weight  Container Information  Package Level 1 Units  Package Level 1 Depth / Length	1 piece 85365080 Finland (Fi 226 mm 220 mm 105 mm 3.0 kg box 1 piece 250 mm 290 mm
Information  Ordering  Minimum Order Quantity  Customs Tariff Number  Country of Origin  Dimensions  Product Net Width  Product Net Weight  Product Net Weight  Product Net Weight  Container Information  Package Level 1 Units  Package Level 1 Depth /  Length  Package Level 1 Depth /  Length Package Level 1 Height	1 piece 85365080 Finland (Fi 226 mm 220 mm 105 mm 3.0 kg box 1 piece 250 mm 290 mm
Information Ordering Minimum Order Quantity Customs Tariff Number Country of Origin Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Container Information	1 piece 85365080 Finland (Fl 226 mn 220 mn 105 mn 3.0 kg box 1 piece 250 mn 290 mn

2/4

© 2025 ABB. All rights reserved.

Number of Poles	3F
Power Loss	at Rated Operating Conditions per Pole 25 W
Rated Impulse	12 kV
Withstand Voltage (U <sub>imp</sub>	
)	
Rated Operational	Main Circuit 1000
Voltage	
Rated Short-time	for 1 s 15 k/
Withstand Current Low	
Voltage (I <sub>cw</sub> )	
Standards	UL 98 / CSA C22.2 NO.
Technical UL/CSA	
Maximum Operating	1000 \
Voltage UL/CSA	1000
Ampere Rating	2007
Ampere Rating	200 .
Ampere Rating Certificates and Declarations	2007

Conformity - CE UL Certificate

cULus certificate OT200-400

## External Classifications and Standards

Object Classification Code WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Disconnectors

Q

