

Accessories

Optional handles

Extended shafts

Auxiliary contacts

UL-types UL98B



OTDC100U02

OTDC100US02

OTDC100U11

OTDC100US11

OTDC100U22

OTDC100US22

OTDC200U02

OTDC200US02

OTDC200U11

OTDC200US11

OTDC180U22

OTDC180US22

U_e [V DC]

1000

1000

1000

1000

1000

1000

Rated current [A]

100 200

100 200

100 200

100 200

100 180

100 180

UL-types UL98B



OTDC250U02

OTDC250U11

OTDC250U22

OTDC250US02

OTDC250US11

OTDC250US22

OTDC320U02

OTDC320U11

OTDC320U22

OTDC320US02

OTDC320US11

OTDC320US22

OTDC400U02

OTDC400U11

OTDC400U22

OTDC400US02

OTDC400US11

OTDC400US22

U_e [V DC]

1000

1000

1000

1000

1000

1000

Rated current [A]

250 320 400

250 320 400

250 320 400

250 320 400

250 320 400

250 320 400

Ordering information

Front operated switch-disconnectors

OTDC100...200US02



OTDC100...200U02




OTDC100...200US11




OTDC100...200U22




OTDC100US_, OTDC200US_




OTDC100U_, OTDC200U_



OTDC100...180US22



OTDC100...180U22_



Disconnect switches OTDC_, UL types, base mounting

The type and ordering numbers are for one piece, including terminal bolt kit. Shafts and handles are not included. OTDC100...200US types are equipped with a short circuit link.

Up to 1000 VDC

Number of poles	Rated current [A] UL98B / 1000 V	Type	Order number	Delivery batch [pcs]	Weight/unit [kg]
Mechanism at the end of the switch, includes the short circuit link					
2	100	OTDC100US02	1SCA126155R1001	1	1.2
2	200	OTDC200US02	1SCA126121R1001	1	1.2
Mechanism at the end of the switch					
2	100	OTDC100U02	1SCA126184R1001	1	1.1
2	200	OTDC200U02	1SCA126123R1001	1	1.1
Mechanism between the poles, includes the short circuit link					
2	100	OTDC100US11	1SCA125437R1001	1	1.2
2	200	OTDC200US11	1SCA125436R1001	1	1.2
Mechanism between the poles					
2	100	OTDC100U11	1SCA123957R1001	1	1.1
2	200	OTDC200U11	1SCA123767R1001	1	1.1

Double circuit use, 1000 VDC

Mechanism between the poles					
2 x 2	100	OTDC100U22	1SCA126180R1001	1	2.3
2 x 2	180	OTDC180U22	1SCA126941R1001	1	2.3
Mechanism between the poles, includes the short circuit links					
2 x 2	100	OTDC100US22	1SCA126181R1001	1	2.5
2 x 2	180	OTDC180US22	1SCA126942R1001	1	2.5

Shafts and handles

Switches with direct mount handle (K) available. To order shafts and handles separately, see pages 21-24.

Switches	Included shaft	Included handle	Included terminal bolts
OTDC100...200_	-	-	M8 x 25
OTDC200...200_K	-	OTDV250EK	M8 x 25