



PRODUCT-DETAILS

# OTDC25UT2

## OTDC25UT2 PV Disconnect Switch



General Information	
Extended Product Type	OTDC25UT2
Product ID	1SCA134388R1001
EAN	6417019631868
Catalog Description	OTDC25UT2 PV Disconnect Switch
Long Description	OTDC25UT2 PV Disconnect Switch, Terminal bolt kit included, Handle and shaft need to be ordered separately, Door mounting, UL 600 VDC 25 A single circuit, IEC 660 VDC 25 A single circuit, IEC 1000 VDC 16 A single circuit

ABB EcoSolutions	
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC301321D0201

## Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301086M0204
Mechanical Drawings	otdc16-32ut-ust2.igs 1SCC307473F0001 1SCC307474F0001

## Environmental

Degree of Protection	Front IP20
Pollution Degree	3

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Estonia (EE)

## Dimensions

Product Frame Size	XS
Product Net Width	73.8 mm 2.9 in
Product Net Height	54.8 mm 2.2 in
Product Net Depth / Length	64.1 mm 2.5 in
Product Net Weight	0.2 kg 0.4 lb

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	100 mm 3.9 in
Package Level 1 Depth / Length	64 mm 2.5 in
Package Level 1 Height	100 mm 3.9 in
Package Level 1 Gross Weight	0.2 kg 0.4 lb
Package Level 1 EAN	6417019631868

## Technical

Cable Cross-Section	2.5 ... 16 mm <sup>2</sup> 12 ... 6 AWG
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 50 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 40 A
Degree of Protection	Front IP20
Handle Type	Handle and shaft not included
Mounting Type	Door mounting
Number of Circuits	1
Number of Poles	2P
Operating Mode	Front Operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Positive Opening Operation Torque (Direct Opening Action)	0.4 ... 0.8 N·m
Power Loss	at Rated Operating Conditions per Pole 0.2 W
Protection Type	UL508i RK5 fuselink max. 70A, IEC60947 gPV fuselink max. 80A
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(1000 V DC) 10 kA
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Current DC-21B ( $I_e$ )	(660 V) 25 A (1000 V) 16 A
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1000 V DC) 1 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	(1000 V DC) 1 kA for 1 s 1 kA
Recommended Screw Driver	Main Circuit Torx
Shaft Diameter	6 mm 0.24 in
Special Functions	No
Standards	UL508i and IEC 60947-1, -3
Switches Operating Mechanism	Mechanism on Top of the Switch
Terminal Type	Screw Terminals
Tightening Torque	Main Circuit 1.2 ... 1.4 N·m
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B)
Wire Stripping Length	Main Circuit 67 ... 11 mm

### Technical UL/CSA

Maximum Operating Voltage	600Vdc, UL 508i
Ampere Rating	25A, 600Vdc, UL508i
Wire Stripping Length	Main Circuit 67 ... 11 mm
Recommended Screw	Main Circuit Torx

Driver	
Tightening Torque	Main Circuit 1.2 ... 1.4 N·m

Certificates and Declarations

CCC Certificate	CQC2012010302579872
Declaration of Conformity - CE	1SCC301192D2704
Declaration of Conformity - UKCA	1SCC301313D0201
DNV GL Certificate	1SCC301231D0201
UL Certificate	UL certificate OTDC16-32.pdf

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

