



PRODUCT-DETAILS

# OTDC600UFV11

## OTDC600UFV11 PV Disconnect Switch



General Information	
Extended Product Type	OTDC600UFV11
Product ID	1SCA158239R1001
EAN	6417019873442
Catalog Description	OTDC600UFV11 PV Disconnect Switch
Long Description	<p>A fully optimized two-pole DC switch-disconnector for 1500V utility-scale photovoltaic power plants covering 315-630A current range. The new design offers both a size reduction and an increase in efficiency and performance to help manufacturers adapt to the industry's rapid adoption of 1500V DC solutions.</p> <p>The two-pole 1500V DC concept helps manufacturers improve system efficiency, reducing switch losses by up to 35 percent. Measuring just 150mm wide and 122mm high, the OTDC range of 1500V DC switches is also up to 30 percent smaller than conventional solutions. The compact size of the new OTDC range makes it possible for manufacturers to reduce the size of combiner boxes and inverters.</p> <p>Main characteristics for this particular OTDC type:</p> <p>Disconnect single PV circuit, Approved according to UL98B and IEC 60947-1,-3</p>

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available

Waste To Landfill Target		
End Of Life		1SCC301112M0201
Disassembling		
Instructions		
Environmental Product		1SCC301247D0201
Declaration - EPD		
Improved Energy	Product Efficiency - Product considered more energy-efficient compared	
Efficiency for Customers	to similar product on market or older products from the same line	
Recyclability Rate of the	Design for Closing Resource Loops - Standard EN45555 - 59,09 %	
Product acc. to EN45555		

Material Compliance

Conflict Minerals		9AKK108467A5658
Reporting Template		
(CMRT)		
REACH Declaration		1SCC301240D0201
RoHS Information		1SCC301239D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Toxic Substances		1SCC301321D0201
Control Act - TSCA		

Popular Downloads

Data Sheet, Technical		1SCC301022C0201
Information		
Instructions and		1SCC301099M0201
Manuals		9AKK107492A6191
Mechanical Drawings	OTDC250-600UFV11_stp	
	OTDC250-600UFV11_igs	
	1SCC307658F0001	
	1SCC307659F0001	
Wiring Diagram		1SCC301030K0201
Environmental Product		1SCC301247D0201
Declaration - EPD		

Environmental

Degree of Protection	Front IP20
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85353010
Country of Origin	Finland (FI)

Dimensions

Product Frame Size	M
Product Net Width	157.5 mm
	6.2 in
Product Net Height	211 mm
	8.3 in
Product Net Depth /	135 mm
Length	5.3 in

Product Net Weight	3.5 kg
	7.7 lb

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	220 mm
	8.7 in
Package Level 1 Depth / Length	250 mm
	9.8 in
Package Level 1 Height	210 mm
	8.3 in
Package Level 1 Gross Weight	3.8 kg
	8.3 lb
Package Level 1 EAN	6417019873442

## Technical

Connection Configuration	Single circuit 2a, 2b
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 630 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 630 A
Degree of Protection	Front IP20
Handle Type	Handle and shaft not included
Mechanical Durability	10000 cycle
Mounting Type	Base mounting
Number of Circuits	1
Number of Poles	2P
Operating Mode	Front Operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Positive Opening Operation Torque (Direct Opening Action)	11 ... 19 N·m
Power Loss	at Rated Operating Conditions per Pole 30 ... 32 W
Protection Type	Circuit breaker
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1500 V
Rated Operational Current DC-21B ( $I_e$ )	(1500 V) 630 A
Rated Operational Current DC-22B	(1500 V) 400 A
Rated Operational Current DC-PV1	(1500 V) 500 A
Rated Operational Current DC-PV2	(1500 V) 500 A
Rated Operational Voltage	1500 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1500 V DC) 10 kA
Rated Short-time Withstand Current Low	(1500 V DC) 10 kA for 1 s 10 kA

Voltage (I <sub>cw</sub> )	
Shaft Diameter	12 mm 0.47 in
Special Functions	No
Standards	UL98B and IEC 60947-1, -3
Switches Operating Mechanism	Mechanism Between the Poles 11 (Between the Poles)
Terminal Type	Lug terminals
Terminal Width	30 mm 1.2 in
Tightening Torque	Cable Lug 50 ... 75 N·m Cable Lug 443 ... 664 lbf·in
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B) Switching of mixed resistive and inductive loads, including moderate overloads (i.e. shunt motors) - occasional actuation (DC-22B) Switching of single PV string(s) without reverse and overcurrents (DC-PV1) Switching of several PV string(s) with reverse and overcurrents (DC-PV2)

### Technical UL/CSA

Maximum Operating Voltage	1500Vdc, UL 98B
Ampere Rating	600A,1500Vdc,UL98B
Short-Circuit Current Rating (SCCR)	Any UL Listed Fuses or Circuit-Breakers 10 kA
Tightening Torque	Cable Lug 50 ... 75 N·m Cable Lug 443 ... 664 lbf·in

### Certificates and Declarations

CCC Certificate	CQC2019010302206498
Declaration of Conformity - CE	1SCC301227D2701
Declaration of Conformity - UKCA	1SCC301313D0201
DNV GL Certificate	1SCC301231D0201
UL Certificate	UL certificate OTDC250-1000UF

### External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

