




PRODUCT-DETAILS

OTM2000E3CM24D

OTM2000E3CM24D MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM2000E3CM24D
Product ID	1SCA113695R1001
EAN	6417019462974
Catalog Description	OTM2000E3CM24D MOTORIZED C/O SWITCH
Long Description	OTM2000E3CM24D MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

ABB EcoSolutions	
End Of Life Disassembling Instructions	1SCC303061M0201
Environmental Information	1SCC303036D0202
Environmental Product Declaration - EPD	1SCC303112D0201

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201

RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204
Environmental Product Declaration - EPD	1SCC303112D0201

Environmental

Degree of Protection	Front IP20
Environmental Information	1SCC303036D0202
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	645 mm 25.39 in
Product Net Height	377 mm 14.84 in
Product Net Depth / Length	335 mm 13.19 in
Product Net Weight	78 kg 171.96 lb

Container Information

Package Level 1 Units	box 1 box
Package Level 1 Width	580 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	500 mm
Package Level 1 Gross Weight	78 kg
Package Level 1 EAN	6417019462974

Technical

Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ °C } 2000\text{ A}$
Degree of Protection	Front IP20
Distance Between Phases	Standard
Handle Color	Black
Handle Type	Direct mounted handle
Motor Operational Voltage	24 V DC
Mounting Type	Base mounting
Number of Poles	3P
Operating Mode	Front operated

Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 55 W
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21B (I_e)	(380 ... 415 V) 2000 A (500 V) 2000 A
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 55 kiloampere rms
Switches Operating Mechanism	Mechanism at the End of the Switch
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Transition Type	Open

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
-------------------	--------------------------------

Certificates and Declarations

Declaration of Conformity - CE	1SCC303038D2702
--------------------------------	-----------------

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122214
IDEA Granular Category Code (IGCC)	5208 >> Controller switch
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3641799

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized Change-over Switches

