



PRODUCT-DETAILS

# OTP16T3M

## OTP16T3M Safety switch



General Information	
Extended Product Type	OTP16T3M
Product ID	1SCA022400R9910
EAN	6417019130842
Catalog Description	OTP16T3M Safety switch
Long Description	<p>Safety switch, 3-p. 415V AC23 16A, 7.5kW. Mounted auxiliary contact: 1NO0NC. Plastic enclosure. IP65. Black Selector handle. Interlocked cover. Defeatable interlocking. The enclosure in the OTP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallell cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal.</p>

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201

RoHS Information	1SCC340075D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC340095D0201

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340002M0012
Mechanical Drawings	OTPK151385SM25.stp

Environmental

Degree of Protection	acc. to IEC 60529 IP65
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Lithuania (LT)

Dimensions

Product Net Width	130 mm
Product Net Height	150 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.453 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	142 mm
Package Level 1 Depth / Length	167 mm
Package Level 1 Height	130 mm
Package Level 1 Gross Weight	0.5 kg
Package Level 1 EAN	6417019130842

Technical

Cable Cross-Section	0.75 ... 10 mm²
Cable Entry Position	Top and/or Bottom
Cable Outlets Per Side	2xM25+M16 / 2xM25+M16
Connecting Capacity Main Circuit	Screw Clamp 0.75 ... 10 mm² Screw Clamp / PE Terminal 2pc,1.5 ... 10 mm²
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 40 A
Degree of Protection	acc. to IEC 60529 IP65

Enclosure Material	Plastic
Handle Color	Black
Handle Type	Selector handle
Impact Resistance Rating	Housing IK08
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	1 NO, 0 NC
Neutral Type	Fixed neutral
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Poles	3P
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Power Loss	at Rated Operating Conditions per Pole 1.6 W
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 750 V
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 ... 415 V) 32 A (500 V) 32 A (690 V) 32 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 10 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(380 ... 415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> )	(690 V AC) 0.705 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 0.5 kA
Recommended Screw Driver	Main Circuit Pozidriv 2
Standards	IEC 60947-1, -3
Tightening Torque	Main Circuit 0.8 N·m
Wire Stripping Length	10 mm

## Technical UL/CSA

Wire Stripping Length	10 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Tightening Torque	Main Circuit 0.8 N·m

## Certificates and Declarations

BV Certificate	1SCC340018D0204
Declaration of Conformity - CE	1SCC340003D2704

External Classifications and Standards		
Object Classification Code		Q
ETIM 8	EC000216 - Switch disconnecter	
ETIM 9	EC000216 - Switch disconnecter (low voltage)	
UNSPSC		39122205
IDEA Granular Category Code (IGCC)	5166 >> Safety switch	
eClass		V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Finland)		3642253
E-Number (Norway)		1428950
E-Number (Sweden)		3140150

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

