

## Type MS116 Accessories

5



HK1-11



HKF1-11



SK1-11



UA1-120



OTPA116



12644

### Auxiliary contact blocks for Type MS116 (side mount)

| Contact configuration | Catalog number |
|-----------------------|----------------|
| 1 NO & 1 NC           | HK1-11         |
| 2 NO                  | HK1-20         |
| 2 NC                  | HK1-02         |

### Auxiliary contact blocks for Type MS116 (front mount)

| Contact configuration | Catalog number |
|-----------------------|----------------|
| 1 NO & 1 NC           | HKF1-11        |

### Bell alarm contact blocks for Type MS116

| Contact configuration | Catalog number |
|-----------------------|----------------|
| 1 NO & 1 NC           | SK1-11         |
| 2 NO                  | SK1-20         |
| 2 NC                  | SK1-02         |

### Undervoltage trip for Type MS116

| Voltage (VAC) | Catalog number |
|---------------|----------------|
| 24            | UA1-24         |
| 48            | UA1-48         |
| 60            | UA1-60         |
| 120           | UA1-120        |
| 230           | UA1-230        |
| 400           | UA1-400        |
| 415           | UA1-415        |

### Undervoltage trip with 1NO & 1NC auxiliary contact for Type MS116

| Voltage (VAC) | Catalog number |
|---------------|----------------|
| 24            | UA1-HK-24      |
| 48            | UA1-HK-48      |
| 60            | UA1-HK-60      |
| 120           | UA1-HK-120     |
| 230           | UA1-HK-230     |
| 400           | UA1-HK-400     |
| 415           | UA1-HK-415     |

### Locking device for Type MS116

| Description  | Catalog number |
|--|----------------|
| Adaptor for padlock Type SA1                             | MS325-SA1      |
| Complete padlock locking kit (adaptor, padlock & 3 keys) | MS325-SA3      |

### Molded plastic enclosures for Type MS116

| Item description                          | Protection level | Catalog number |
|---|------------------|----------------|
| Gray enclosure with black handle          | IP64             | OTPA116L2P1    |
| Yellow enclosure with red handle          | IP64             | OTPA116A2P1    |
| Gray enclosure with clear cover, 4 module | IP55             | 12644          |
| Gray enclosure with clear cover, 6 module | IP55             | 12646          |
| Gray enclosure with black handle          | IP65             | IB116-G        |
| Yellow enclosure with red handle          | IP65             | IB116-Y        |

### Plastic adaptors for enclosures for Type MS116

| Description    | Catalog number |
|----------------|----------------|
| PG16 to 1/2NPT | PG16-1/2NPT    |

### Shunt trip for Type MS116

| Voltage (VAC) | Catalog number |
|---------------|----------------|
| 24V           | AA1-24         |
| 110V          | AA1-110        |
| 200 – 240V    | AA1-230        |
| 350 – 415V    | AA1-400        |