



Reference: OVRPV40600P
Code: 2CTB803953R5300

OVR PV 40 600P



OVR PV 40 600P

Ordering

Product Main Type:	T2
EAN:	3660308516510
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363090

Technical

Number of Protected Poles:	2
Arrester Class:	II
Standards:	EN 50539-11
Remote Indicator:	No
Version:	Plug-in
Discharge Current (I_{max}):	Nominal 20 kA Maximum 40 kA
Impulse Current:	2 kA
Maximum Continuous Operating Voltage (U_c):	670 V
Voltage Rating DC:	670 V

Voltage Protection Level (Up):	(L-N) 2.8 kV (N-PE) 2.8 kV (L-PE) 2.8 kV
Short Circuit Withstand Icc:	0,3 kA
Product Name:	Surge Protective Devices
Suitable For:	To protect the systems against the transient overvoltage (lightning)

Dimensions

Product Net Width:	53,4 mm
Product Net Depth:	64,8 mm
Product Net Height:	85 mm
Product Net Weight:	375 g
Width in Number of Modular Spacings:	3

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	117 mm
Package Level 1 Length:	61 mm
Package Level 1 Height:	82 mm
Package Level 1 Gross Weight:	400 g
Package Level 1 EAN:	3660308516510

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CTC432078D1701
Declaration of Conformity - CE:	2CTC436004G1701
Instructions and Manuals:	2CTC432008M1701

Classifications

ETIM 4:	EC000941 - Surge protection device for power supply systems
ETIM 5:	EC000941 - Surge protection device for power supply systems