



SIEMENS LOW VOLTAGE PL SERIES LOAD CENTER. MAIN LUG WITH 20 1-Inch Spaces ALLOWING MAX 30 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(150A) 100KA INTERRUPT. SPECIAL FEATURES: COPPER BUS, INTERCHANGEABLE MAIN, SPLIT GROUND, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE. REPLACED BY PN2040L1150C. AVAILABLE 4/1/2020

| General technical data | |
|--|--------------|
| configuration of the busbars | 150A |
| fastening method | Surface |
| phase number | 1 |
| suitability for operation | Residential |
| Electricity | |
| ampacity | 150 A |
| voltage between phase and Ground (GND) rated value | 120 V |
| voltage between phase and phase rated value | 240 V |
| Switching capacity | |
| switching capacity current according to EN 60898 rated value | 22000 A |
| Model | |
| product brand name | Siemens |
| product sub brand name | Load Centers |
| product type designation | 1 |
| type of wiring of distribution board | 3w |
| Mechanical Design | |
| number of modular width units for installation width | 20 |
| width [in] | 2426.5 in |

last modified:

6/18/2021 

