



Figure similar

SIEMENS LOW VOLTAGE PL SERIES LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING MAX 54 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (200A) 100KA INTERRUPT. SPECIAL FEATURES: COPPER BUS, INTERCHANGEABLE MAIN, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.

| General technical data                                       |              |
|--------------------------------------------------------------|--------------|
| configuration of the busbars                                 | 200A         |
| fastening method                                             | Combination  |
| phase number                                                 | 3            |
| suitability for operation                                    | Residential  |
| Electricity                                                  |              |
| ampacity                                                     | 200 A        |
| voltage between phase and Ground (GND) rated value           | 120 V        |
| voltage between phase and phase rated value                  | 240 V        |
| Switching capacity                                           |              |
| switching capacity current according to EN 60898 rated value | 22000 A      |
| Model                                                        |              |
| product brand name                                           | Siemens      |
| product sub brand name                                       | Load Centers |
| product type designation                                     | 1            |
| type of wiring of distribution board                         | 3/4w         |
| Mechanical Design                                            |              |
| number of modular width units for installation width         | 30           |

last modified:

1/6/2021 

