



Figure similar

SIEMENS LOW VOLTAGE PL SERIES LOAD CENTER. MAIN LUG WITH 40 1-Inch Spaces ALLOWING MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(200A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, INTERCHANGEABLE MAIN, SPLIT GROUND, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE. REPLACED BY PN4040L1200. AVAILABLE 4/1/2020

General technical data

configuration of the busbars	200
number of circuits in a trunking unit	40
phase number	1

Electricity

ampacity	200 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V

Switching capacity

switching capacity current according to EN 60898 rated value	100 A
--	-------

Model

product brand name	Siemens
product type designation	Series PL, Split Ground, Main Lug/Convertible, Special Application
special product feature	Features: Invertible for bottom feed application, Provided with 2 factory installed ground bars, Combination head screw on the neutrals, ground, trim, upper pan, and bond screw provide installation flexibility, The prepositioned bond screw eliminates bond
type of wiring of distribution board	3-Wire SN

Mechanical Design

depth [in]	36 in
height [in]	3.13 in
number of modular width units for installation width	40
size of the circuit-breaker	MBK150A Or MBK200A Field Installed
width [in]	14.5 in

General product approval

certificate of suitability	UL Listed
----------------------------	-----------

last modified: 6/18/2021 

