



SIEMENS LOW VOLTAGE PL SERIES UNASSEMBLED LOAD CENTER. MAIN LUG INTERIOR WITH 12 1-INCH SPACES ALLOWING MAX 24 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (200A) 100KA INTERRUPT. SPECIAL FEATURES: COPPER BUS, INTERCHANGEABLE MAIN, VALUE PACK.

| General technical data                                       |                                                       |
|--------------------------------------------------------------|-------------------------------------------------------|
| configuration of the busbars                                 | 200                                                   |
| number of circuits in a trunking unit                        | 24                                                    |
| phase number                                                 | 3                                                     |
| Electricity                                                  |                                                       |
| ampacity                                                     | 200 A                                                 |
| Switching capacity                                           |                                                       |
| switching capacity current according to EN 60898 rated value | 100 A                                                 |
| Model                                                        |                                                       |
| product brand name                                           | Siemens                                               |
| product type designation                                     | Main Lug, Bulk, Interior                              |
| special product feature                                      | Bus Bar Type: Tin Plated Copper                       |
| type of wiring of distribution board                         | 3 or 4-Wire SN                                        |
| Mechanical Design                                            |                                                       |
| height [in]                                                  | 10.04 in                                              |
| number of modular width units for installation width         | 12                                                    |
| size of the circuit-breaker                                  | MBK3100, MBK3125, MBK3175, or MBK3200 Field Installed |
| width [in]                                                   | 9.95 in                                               |
| General product approval                                     |                                                       |
| certificate of suitability                                   | UL Listed                                             |

last modified: 6/18/2021 

