


## PRODUCT-DETAILS

# PS3-3-0

## PS3-3-0 Busbar



### General Information

|                       |                                  |
|-----------------------|----------------------------------|
| Extended Product Type | PS3-3-0                          |
| Product ID            | 1SAM101937R0013                  |
| EAN                   | 4013614313837                    |
| Catalog Description   | PS3-3-0 Busbar                   |
| Long Description      | PS3-3-0 Busbar for for 3 devices |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85369010 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100173C0201 |
| Instructions and Manuals          | 2CDC131005M5703 |

### Dimensions

|                     |          |
|---------------------|----------|
| Product Net Width   | 152.5 mm |
| Product Net Height  | 31.5 mm  |
| Product Net Depth / | 13 mm    |

Length

|                    |          |
|--------------------|----------|
| Product Net Weight | 0.062 kg |
|--------------------|----------|

## Technical

|                                                                   |                                                                  |
|-------------------------------------------------------------------|------------------------------------------------------------------|
| Rated Operational Voltage                                         | 690 V                                                            |
| Rated Operational Current (I <sub>e</sub> )                       | 63 A                                                             |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )               | 6 kV                                                             |
| Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> ) | 100 kA                                                           |
| Number of Mountable Devices                                       | 3                                                                |
| Number of Lateral Auxiliary Contacts                              | 0                                                                |
| Number of Phases                                                  | 3                                                                |
| Number of Poles                                                   | 9                                                                |
| Degree of Protection                                              | IP20                                                             |
| Pollution Degree                                                  | 3                                                                |
| Connection Type                                                   | Pin                                                              |
| Standards                                                         | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>UL 60947-1<br>UL 60947-4-1 |
| Product Name                                                      | Busbar                                                           |
| Suitable For                                                      | MS325<br>MO325                                                   |
| Suitable for Product Class                                        | Manual Motor Starter                                             |
| Accessory Group                                                   | Electrical                                                       |
| Accessory Type                                                    | 3-Phase Busbar                                                   |

## Technical UL/CSA

|                                  |                       |
|----------------------------------|-----------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC |
| Ampere Rating UL/CSA             | 63 A                  |

## Environmental

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Ambient Air Temperature | Operation -20 ... +50 °C<br>Storage -20 ... +70 °C              |
| RoHS Status             | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Certificates and Declarations (Document Number)

|                                  |                 |
|----------------------------------|-----------------|
| cUL Certificate                  | 1SAA963001-1701 |
| Declaration of Conformity - CE   | 1SAD938515-0056 |
| Declaration of Conformity - UKCA | 1SAD938502-1056 |
| Instructions and Manuals         | 2CDC131005M5703 |
| RoHS Information                 | 1SAD938511-0056 |
| UL Certificate                   | 1SAA963001-1602 |

| Container Information          |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 46 mm         |
| Package Level 1 Depth / Length | 171 mm        |
| Package Level 1 Height         | 80 mm         |
| Package Level 1 Gross Weight   | 0.66 kg       |
| Package Level 1 EAN            | 4013614487927 |
| Package Level 1 Units          | box 10 piece  |

| Classifications                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| Object Classification Code         | W                                                        |
| ETIM 4                             | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5                             | EC000215 - Phase busbar                                  |
| ETIM 6                             | EC000215 - Phase busbar                                  |
| ETIM 7                             | EC000215 - Phase busbar                                  |
| ETIM 8                             | EC000215 - Phase busbar                                  |
| eClass                             | V11.0 : 27371306                                         |
| UNSPSC                             | 39121117                                                 |
| IDEA Granular Category Code (IGCC) | 4378 >> Phase busbar                                     |

| Categories                                                                                                      |  |
|-----------------------------------------------------------------------------------------------------------------|--|
| Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories |  |

