



Figure similar

SIEMENS LOW VOLTAGE RISER LOAD CENTER. MAIN LUG WITH 24 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A) 100KA INTERRUPT. SPECIAL FEATURES: COPPER BUS, INTERCHANGEABLE MAIN, GRAY TRIM.

General technical data

configuration of the busbars	125
number of circuits in a trunking unit	42
phase number	1
suitability for operation	For High Rise Applications

Electricity

ampacity	125 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V

Switching capacity

switching capacity current according to EN 60898 rated value	100 A
--	-------

Model

product brand name	Siemens
product type designation	Riser Panel, Main Lug/Convertible
special product feature	Features: Neutrals aligned on left side- keeps way clear for riser cables, Invertible for left and right hand applications, UL Listed for use in 1 and 3 phase riser gutter applications, The shifted interior provides room for conductors to pass through the
type of wiring of distribution board	3-Wire SN

Mechanical Design

depth [in]	30 in
height [in]	3.88 in
number of modular width units for installation width	24
size of the circuit-breaker	MBK100A, MBK125A
width [in]	14.25 in

General product approval

certificate of suitability	UL Listed
----------------------------	-----------

last modified: 6/18/2021 

