



Figure similar

SIEMENS LOW VOLTAGE RISER LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, INTERCHANGEABLE MAIN, GRAY TRIM.

## General technical data

|                              |             |
|------------------------------|-------------|
| configuration of the busbars | 200A        |
| fastening method             | Combination |
| phase number                 | 1           |
| suitability for operation    | Residential |

## Electricity

|  |       |
|--|-------|
| ampacity   | 200 A |
| voltage between phase and Ground (GND) rated value | 120 V |
| voltage between phase and phase rated value        | 240 V |

## Switching capacity

|  |         |
|--|---------|
| switching capacity current according to EN 60898 rated value | 22000 A |
|--|---------|

## Model

|                                      |              |
|--------------------------------------|--------------|
| product brand name                   | Siemens      |
| product sub brand name               | Load Centers |
| type of wiring of distribution board | 3w           |

## Mechanical Design

|  |          |
|--|----------|
| depth [in]   | 36 in    |
| height [in]  | 36 in    |
| number of modular width units for installation width | 30       |
| width [in]   | 32203 in |

last modified:

6/18/2021 

