Product data sheet

Specification





dual function relay, Harmony Timer Relays, 5A, 1 CO, 0.05s…300s, delay on and pulse on de energization, 24...240V AC DC

RE22R1MKMR

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 83.09 USD

Main

| Range Of Product | Harmony Timer Relays | |
|---------------------------|----------------------|--|
| Product Or Component Type | Modular timing relay | |
| Discrete Output Type | Relay | |
| Device Short Name | RE22 | |
| Nominal Output Current | 5 A | |

Complementary

| Contacts Type And Composition | 1 C/O timed contact, cadmium free |
|--------------------------------|---|
| Time Delay Type | Pulse-on de-energization Delay on de-energization |
| Time Delay Range | 0.33 s 0.050.5 s 330 s 0.11 s 30300 s 10100 s 110 s |
| Control Type | Rotary knob |
| [Us] Rated Supply Voltage | 24240 V AC/DC 50/60 Hz |
| Release Input Voltage | <= 2.4 V |
| Voltage Range | 0.851.1 Us |
| Supply Frequency | 5060 Hz +/- 5 % |
| Connections - Terminals | Screw terminals, 1 x 0.51 x 3.3 mm² AWG 20AWG 12) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm² AWG 20AWG 14) solid without cable end Screw terminals, 1 x 0.21 x 2.5 mm² AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm² AWG 24AWG 16) flexible with cable end |
| Tightening Torque | 5.318.85 lbf.in (0.61 N.m) IEC 60947-1 |
| Housing Material | Self-extinguishing |
| Repeat Accuracy | +/- 0.5 % IEC 61812-1 |
| Temperature Drift | +/- 0.05 %/°C |
| Voltage Drift | +/- 0.2 %/V |
| Setting Accuracy Of Time Delay | +/- 10 % of full scale 25 °C IEC 61812-1 |
| Insulation Resistance | 100 MOhm 500 V DC IEC 60664-1 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Recovery Time | 50 ms on de-energisation |
|---------------------------------|--|
| Immunity To Microbreaks | 10 ms |
| Power Consumption In Va | 3 VA 240 V AC |
| Power Consumption In W | 2 W 240 V DC |
| Switching Capacity In Va | 1250 VA |
| Minimum Switching Current | 10 mA 5 V DC |
| Maximum Switching Current | 5 A |
| Maximum Switching Voltage | 250 V AC |
| Electrical Durability | 100000 cycles, 2 A at 24 V, DC-1 100000 cycles, 5 A at 250 V, AC-1 |
| Mechanical Durability | 10000000 cycles |
| Rated Impulse Withstand Voltage | 5 kV 1.250 μs IEC 60664-1 |
| Power On Delay | 100 ms |
| Creepage Distance | 4 kV/3 IEC 60664-1 |
| Overvoltage Category | III IEC 60664-1 |
| Safety Reliability Data | B10d = 180000 MTTFd = 194 years |
| Mounting Position | Any position |
| Mounting Support | 35 mm DIN rail conforming to IEC 60715 |
| Status Led | Green LED backlight steady)dial pointer indication Yellow LED steady)output relay energised Yellow LED steady)power ON |
| Function Available | He-Pulse-on de-energization-1 C/O K-Delay on de-energization (without auxiliary supply)-1 C/O |
| Width | 0.89 in (22.5 mm) |
| Net Weight | 0.22 lb(US) (0.1 kg) |
| Control Type | With test button |
| Number Of Functions | 2 |

Environment

| Dielectric Strength | 2.5 kV 1 mA/1 minute 50 Hz between relay output and power supply basic insulation |
|--|---|
| | IEC 61812-1 |
| Standards | IEC 61812-1 |
| | UL 508 |
| Directives | 2006/95/EC - low voltage directive |
| | 2004/108/EC - electromagnetic compatibility |
| Product Certifications | GL |
| | UL |
| | CSA |
| | RCM |
| | CCC |
| | CE |
| | EAC |
| Ambient Air Temperature For Operation | -4140 °F (-2060 °C) |
| Ambient Air Temperature For Storage | -40158 °F (-4070 °C) |
| Ip Degree Of Protection | IP40 housing: conforming to IEC 60529 |
| | IP50 front face: conforming to IEC 60529 |
| | IP20 terminals: conforming to IEC 60529 |

| Pollution Degree | 3 IEC 60664-1 |
|-------------------------------|---|
| Vibration Resistance | 20 m/s² 10150 Hz)IEC 60068-2-6 |
| Shock Resistance | 15 gn not operating 11 ms IEC 60068-2-27 5 gn in operation 11 ms IEC 60068-2-27 |
| Relative Humidity | 95 % 77131 °F (2555 °C) |
| Electromagnetic Compatibility | Fast transients immunity test - test level: 1 kV level 3 (capacitive connecting clip) conforming to IEC 61000-4-4 |
| | Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5 |
| | Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5 |
| | Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 |
| | Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 |
| | Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 (80 MHz1 GHz) conforming to IEC 61000-4-3 |
| | Conducted RF disturbances - test level: 10 V level 3 (0.1580 MHz) conforming to IEC 61000-4-6 |
| | Fast transient bursts - test level: 2 kV level 3 (direct contact) conforming to IEC 61000-4-4 |
| | Immunity to microbreaks and voltage drops - test level: 30 % (500 ms) conforming to IEC 61000-4-11 |
| | Immunity to microbreaks and voltage drops - test level: 100 % (20 ms) conforming to IEC 61000-4-11 |

Ordering and shipping details

| Category | US10CP222376 | |
|-------------------|---------------|--|
| Discount Schedule | 0CP2 | |
| Gtin | 3606480792571 | |
| Returnability | No | |
| Country Of Origin | ID | |

Packing Units

| I acking Office | |
|------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 0.98 in (2.5 cm) |
| Package 1 Width | 3.27 in (8.3 cm) |
| Package 1 Length | 3.74 in (9.5 cm) |
| Package 1 Weight | 3.21 oz (91.0 g) |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 40 |
| Package 2 Height | 5.91 in (15.0 cm) |
| Package 2 Width | 11.81 in (30.0 cm) |
| Package 2 Length | 15.75 in (40.0 cm) |
| Package 2 Weight | 9.01 lb(US) (4.088 kg) |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 640 |
| Package 3 Height | 31.50 in (80.0 cm) |
| Package 3 Width | 31.50 in (80.0 cm) |
| Package 3 Length | 23.62 in (60.0 cm) |

Package 3 Weight

161.78 lb(US) (73.38 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Product data sheet

RE22R1MKMR

Dimensions Drawings

Dimensions




Product data sheet

RE22R1MKMR

Connections and Schema

Wiring Diagram



RE22R1MKMR


Technical Description

Function K: Delay On De-energization without Auxillary Supply

Description


On energisation of power supply, the output(s) R close(s). On de-energisation of power supply, timing period T starts and at the end of this period, the output(s) R revert(s) to its/their initial state. The energization of power supply > Tk is necessary to sustain the timing period T.

Function: 1 Output



Tk > 80ms

Function: 2 Outputs



Tk > 80ms


RE22R1MKMR

Function He: Pulse-on De-energization

Description

After energisation of power supply > 80ms followed by deenergization of power supply, the output(s) R closes() for the duration of a timing period T then revert(s) to its/their initial state. Energisation of power supply < 80ms followed by deenergization of power supply, the output(s) R close(s) and WILL NOT ABLE TO sustain for the duration of a timing period T before revert(s) to its/their initial state.

Function: 1 Output



Legend

