Product datasheet

Specification





star-delta timing relay - 24VDC/ 24..240 V AC - 1 C/O

RE22R1QMU

Main

Range of product	Harmony Timer Relays
product or component type	Modular timing relay
Discrete output type	Relay
Device short name	RE22
Nominal output current	8 A

Complementary

Complementary	Complementary		
Contacts type and composition	1 C/O timed contact		
time delay type	Star-delta		
time delay range	110 min		
	660 s		
	0.11 s		
	110 h		
	110 s		
	660 min		
	10100 h		
Control type	Rotary knob front panel		
[Us] rated supply voltage	24240 V AC		
	24 V DC		
Voltage range	0.851.1 Us		
Supply frequency	5060 Hz +/- 5 %		
Connections - terminals	Screw terminals, 2 x 1.5 mm² with cable end		
	Screw terminals, 2 x 2.5 mm² without cable end		
	Colow terminals, 2 x 2.5 mm without sable ond		
Tightening torque	0.61 N.m conforming to IEC 60947-1		
Housing material	Self-extinguishing		
Repeat accuracy	+/- 0.5 % conforming to IEC 61812-1		
Temperature drift	+/- 0.05 %/°C		
Voltage drift	+/- 0.2 %/V		
Setting accuracy of time delay	+/- 10 % of full scale at 25 °C conforming to IEC 61812-1		
Control signal pulse width	30 ms 100 ms under load		
	100 ms under load		
Insulation resistance	100 MOhm at 500 V DC conforming to IEC 60664-1		
Recovery time	120 ms on de-energisation		
Immunity to microbreaks	10 ms		
Power consumption in VA	50 VA at 240 V AC		
Power consumption in W	0.7 W at 24 V DC		

Breaking capacity	2000 VA
Minimum switching current	10 mA at 5 V
Maximum switching current	8 mA
Maximum switching voltage	250 V
Electrical durability	100000 cycles for resistive load, 8 A at 250 V, AC
Mechanical durability	10000000 cycles
Rated impulse withstand voltage	5 kV for 1.250 μs conforming to IEC 60664-1 5 kV conforming to IEC 61812-1
Power on delay	100 ms
Safety reliability data	MTTFd = 182.6 years B10d = 170000
Mounting position	Any position in relation to normal vertical mounting plane
Mounting support	35 mm DIN rail conforming to IEC 60715
Status LED	LED green (flashing) for timing in progress LED green (steady) for power ON LED yellow for relay energised
Function available	Q-Star-delta relay (2 NO outputs with same common)-1 C/O
Width	22.5 mm
net weight	0.086 kg
Control type	With test button
Number of functions	1

Environment

Dielectric strength	2.5 kV for 1 mA/1 minute at 50 Hz conforming to IEC 61812-1
Standards	IEC 61000-6-4
	IEC 61000-6-2
	IEC 61000-6-3
	IEC 61000-6-1
	IEC 61812-1
Directives	2006/95/EC - low voltage directive
	2004/108/EC - electromagnetic compatibility
Product certifications	CSA
	EAC
	RCM
	CE
	CCC
	GL
	cULus
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-3060 °C
IP degree of protection	IP40 housing: conforming to IEC 60529
	IP20 terminal block: conforming to IEC 60529
	IP40 front face: conforming to IEC 60529
Vibration resistance	20 m/s² (f= 10150 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Relative humidity	93 %, without condensation conforming to IEC 60068-2-30

Electromagnetic compatibility

Electrostatic discharge immunity test - test level: 6 kV level 3 (contact discharge)

conforming to IEC 61000-4-2

Electrostatic discharge immunity test - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 $\,$

Fast transients immunity test - test level: 1 kV level 3 (capacitive connecting clip) conforming to IEC 61000-4-4

Fast transients immunity test - test level: 2 kV level 3 (direct contact) conforming to IEC 61000-4-4

Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5

Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5

Radiated radio-frequency electromagnetic field immunity test - test level: 10 V level 3 (0.15...80 MHz) conforming to IEC 61000-4-6

Electromagnetic field immunity test - test level: 10 V/m level 3 (80 MHz...1 GHz) conforming to IEC 61000-4-3

Immunity to microbreaks and voltage drops - test level: 30 % (500 ms) conforming to IEC 61000-4-11

Immunity to microbreaks and voltage drops - test level: 100 % (20 ms) conforming to IEC 61000-4-11

Conducted and radiated emissions class B conforming to EN 55022

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 cm
Package 1 Width	8.2 cm
Package 1 Length	9.6 cm
Package 1 Weight	98.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.309 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes


Certifications & Standards


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

28-Jun-2024

Dimensions Drawings

Dimensions






Product datasheet


RE22R1QMU

Connections and Schema

Internal Wiring Diagram



Wiring Diagram




RE22R1QMU

Technical Description

Star-delta Timing Relay

Description

After power-up, the star contact closes instantly and timing T starts, At the end of timing period, the star contact opens. After a t ms pause, the delta contact closes and remains in this position.



t: 20, 40, 60, 80, 100, 120, 140 ms

Legend

U:

Supply

Relay de-energised	
Relay energised	
Output open	
Output closed	
R1 :	Star contact output
R2 :	Delta contact output
T:	Timing period
t:	Delay to switch ON Delta contact output