Specifications



() Discontinued

## Industrial timing relay, Zelio Time, symmetrical on and off delay 0.05...1 s, 24 V AC DC, 1 OC

RE7MA11BU

Discontinued on: 20 Oct 2022

## Main

mann	
Range of product	Zelio Time
Product or component type	Industrial timing relay
Component name	RE7
Time delay type	Ac
Time delay range	0.05 s300 h

## Complementary

o emplementary	
Discrete output type	Relay
Contacts material	90/10 silver nickel contacts
Width pitch dimension	22.5 mm
[Us] rated supply voltage	110240 V AC 50/60 Hz 24 V AC/DC 50/60 Hz 4248 V AC/DC 50/60 Hz
Voltage range	0.851.1 Us
Connections - terminals	Screw terminals, 2 x 1.5 mm <sup>2</sup> flexible with cable end Screw terminals, 2 x 2.5 mm <sup>2</sup> flexible without cable end
Tightening torque	0.61.1 N.m
Setting accuracy of time delay	+/- 10 % of full scale
Repeat accuracy	+/- 0.2 %
Temperature drift	< 0.07 %/°C
Voltage drift	< 0.2 %/V
Minimum pulse duration	20 ms
Reset time	50 ms
Maximum switching voltage	250 V AC/DC
Mechanical durability	2000000 cycles
[Ith] conventional free air thermal current	8 A
Maximum [le] rated operational current	2 A DC-13 24 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.1 A DC-13 250 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.2 A DC-13 115 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 3 A AC-15 at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660
Minimum switching capacity	at 12 V 10 mA
Input voltage	< 60 V X1Z2 terminal(s) < 60 V Y1Z2 terminal(s)

Maximum switching current	1 mA (X1Z2) 1 mA (Y1Z2)
Input compatibility	3/4 wires sensors PNP/NPN without internal load <50 m X1Z2 terminal(s) 3/4 wires sensors PNP/NPN without internal load <50 m Y1Z2 terminal(s)
Potentiometer characteristic	Linear 47 kOhm (+/- 20 %), 0.2 W, cable length <25 m Z1Z2 terminal(s)
Marking	CE
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	250 V between contact circuit and control inputs IEC certified 250 V between contact circuit and power supply IEC certified 300 V between contact circuit and control inputs CSA certified 300 V between contact circuit and power supply CSA certified
Supply disconnection value	> 0.1 Uc
Operating position	Any position without derating
Surge withstand	2 kV conforming to IEC 61000-4-5 level 3
Power consumption in VA	0.7 VA at 24 V 1.6 VA at 48 V 1.8 VA at 110 V 8.5 VA at 240 V
Maximum power consumption in W	0.5 W at 24 V 1.2 W at 48 V
Terminal description	(Z1)UNUSED ALT (Y1)UNUSED (X1)UNUSED (15-16-18)OC_ON_OFF (Z2)UNUSED (B1-A2)CO
Height	78 mm
Width	22.5 mm
Depth	80 mm
Net weight	0.15 kg

## Environment

Immunity to microbreaks	3 ms
Standards	EN/IEC 61812-1
Product certifications	UL CSA GL
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-2060 °C
Relative humidity	1585 % 3K3 conforming to IEC 60721-3-3
Vibration resistance	0.35 mm (f= 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP20 (terminals) IP50 (housing)
Pollution degree	3 conforming to IEC 60664-1
Dielectric strength	2.5 kV
Non-dissipating shock wave	4.8 kV
Resistance to electrostatic discharge	6 kV in contact conforming to IEC 61000-4-2 level 3 8 kV in air conforming to IEC 61000-4-2 level 3

Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Disturbance radiated/conducted	CISPR 22 - class A CISPR 11 group 1 - class A

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

# Contractual warranty


Warranty

18 months


**Dimensions Drawings** 

#### Width 22.5 mm

#### **Rail Mounting**



#### **Screw Fixing**




Connections and Schema

#### Internal Wiring Diagram

A1 Z1	15	B1 B2
<u>8</u> 8	1	15
F	니 알	18
X1	Y1	Z2
18	16	A2

#### Recommended Application Wiring Diagram


#### Start by External Control



1 Supply 2 12...48 V 3 24 V

#### Recommended Application Wiring Diagram


#### Start by External Control



1 Supply 2 12...48 V 3 24 V


#### **Control of Several Relays**

Control of several relays with a single external control contact




### RE7MA11BU

#### Connection of an External Control Contact Without Using Terminal Z2



Direct current supply only.


It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.



Direct current supply only.


It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

#### Connection 3-Wire NPN or PNP Sensor




#### Connection 3-Wire NPN or PNP Sensor Without Using Terminal Z2

#### **Connection NPN**




It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

#### **Connection PNP**



It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

#### **Connection of Potentiometer**




**Connection Precautions** 



### UNEXPECTED EQUIPMENT OPERATION

No galvanic isolation between supply terminals and control inputs.

Failure to follow these instructions can result in death, serious injury, or equipment damage.




#### Performance Curves

#### Performance Curves

#### A.C. Load Curve 1

Electrical durability of contacts on resistive loading millions of operating cycles




X Current broken in A

Y Millions of operating cycles

#### A.C. Load Curve 2


Reduction factor k for inductive loads (applies to values taken from durability curve 1).




#### **X** Power factor on breaking (cos $\phi$ )

Y Reduction factor k

Example: An LC1-F185 contactor supplied with 115 V/50 Hz for a consumption of 55 VA or a current consumption equal to 0.1 A and  $\cos \phi = 0.3$ . For 0.1 A, curve 1 indicates a durability of approximately 1.5 million operating cycles. As the load is inductive, it is necessary to apply a reduction coefficient k to this number of cycles as indicated by curve 2. For  $\cos \phi = 0.3$ : k = 0.6 The electrical durability therefore becomes:1.5  $10^6$  operating cycles x 0.6 = 900 000 operating cycles.



D. C. Load Limit Curve



X Current in A

Y Voltage in V

- **1** L/R = 20 ms
- 2 L/R with load protection diode

3 Resistive load

#### **Technical Description**

#### Function Ac : On- and Off-Delay Relay with Control Signal

#### Description


After power-up, closing of the control contact C causes the timing period T to start (timing can be interrupted by operating the Gate control contact G). At the end of this timing period, the relay closes.

When control contact C re-opens, the timing T starts.


At the end of this timing period T, the output reverts to its initial position (timing can be interrupted by operating the Gate control contact G).

The second output can be either timed or instantaneous.

#### Function: 1 Output



#### **Function: 2 Outputs**



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

Life Is On Schneider

#### Legend

Relay de-energised	
Relay energised	
Output open	
Output closed	
с	Control contact
G	Gate
R	Relay or solid state output
R1/R2	2 timed outputs
R2 inst.	The second output is instantaneous if the right position is selected
т	Timing period
Ta -	Adjustable On-delay
Tr -	Adjustable Off-delay
U	Supply