

RL00802

REACTOR DRIVE LINE 3PH 1.5-2HP 208/230V OPEN

Product availability: Non-Stock - Not normally stocked in distribution facility

Complementary

Line Rated Current	8 A
AWG gauge	AWG 22...AWG 14
Depth	121.92 mm (4.8 in)
Electrical connection	Screw clamp terminal
Height	76.20 mm (3 in)
Permissible voltage	600 V AC
Net weight	3.63 kg (8 lb(US))
Protection type	Current protection Harmonic distortion Overvoltage protection
Width	152.40 mm (6 in)

Environment

NEMA degree of protection	No enclosure rating (open device)
Product certifications	CE UL listed file E180243 CSA LR29753

Ordering and shipping details

Category	22062 - LINE REACTORS/FILTERS (RL,KLC)
Discount Schedule	CP4C
GTIN	00785901712206
Package weight(Lbs)	3.18 kg (7 lb(US))
Returnability	No
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.