

Complementary

Line Rated Current	35 A
AWG gauge	AWG 22...AWG 5
Depth	5.8 in (147.32 mm)
Electrical Connection	Screw clamp terminal
Height	4 in (101.60 mm)
Permissible voltage	600 V AC
Net Weight	14 lb(US) (6.35 kg)
Protection Type	Overvoltage protection Current protection Harmonic distortion
Width	7.2 in (182.88 mm)

Environment

NEMA Degree of Protection	No enclosure rating (open device)
Product certifications	UL listed file E180243 CE CSA LR29753

Ordering and shipping details

Category	22062-LINE REACTORS/FILTERS (RL,KLC)
Discount Schedule	CP4C
GTIN	00785901712220
Package weight(Lbs)	14.00 lb(US) (6.350 kg)
Returnability	Yes
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.