

#### Complementary

Line Rated Current	45 A
AWG gauge	AWG 18...AWG 4
Depth	13.09 in (332.49 mm)
Electrical Connection	Screw clamp terminal
Height	13 in (330.20 mm)
Permissible voltage	600 V AC
Net Weight	46 lb(US) (20.87 kg)
Protection Type	Current protection Overvoltage protection Harmonic distortion
Width	13.22 in (335.79 mm)

#### Environment

Product certifications	CE UL listed file E180243 CSA LR29753
------------------------	---

#### Ordering and shipping details

Category	22062-LINE REACTORS/FILTERS (RL,KLC)
Discount Schedule	CP4C
GTIN	00785901143772
Package weight(Lbs)	46.00 lb(US) (20.865 kg)
Returnability	No
Country of origin	US

#### Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.